

ROHS COMPLIANT		PRODUCT DATA DRAWING		REVISION HISTORY			
REV	DESCRIPTION			DATE	APPROVED		
G	DCN 41836			11/15	STW		

MATERIAL:		
BODY, COUPLING NUT:	STAINLESS STEEL PER AMS-5640, ALLOY UNS S30300, TYPE 1	
CONTACT:	BRASS PER ASTM B16, ALLOY UNS No. C36000	
LOCK RING:	BERYLLIUM COPPER PER ASTM B196, ALLOY No. UNS C17300, TD04	
INSULATOR:	TEFLON PER ASTM D1457	
GASKET:	SILICONE RUBBER PER A-A-59588, CLASS 2B, GRADE 50/60	
FINISH:		
BODY & CONTACT:	GOLD PER ASTM B 488, TYPE II, CODE C, CLASS 0.76, OVER NICKEL PER AMS-QQ-N-290, CLASS 1, .00010" MIN.	
COUPLING NUT:	GOLD PER ASTM B 488, TYPE I, CODE C, CLASS 0.50, OVER NICKEL PER AMS-QQ-N-290, CLASS 1, .00010" MIN.	
PERFORMANCE:		
IMPEDANCE:	50 OHMS	
FREQ. RANGE:	DC TO 18.0 GHz	

--	--

MATERIAL:	SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/64 ANGULAR: X° ±1°0'
-----------	-----------	---

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[2902-6005](#)