## PRODUCT DATA DRAWING REVISION HISTORY **ROHS COMPLIANT** DESCRIPTION DCN 40111 -.738 MAX 18.75 MAX -.575 MAX[ 14.61 MAX ] ----.312[7.92] HEX.---**MATERIAL:**

BODY,

PRESS CAP & COUPLING NUT:

STAINLESS STEEL PER AMS-5640,

ALLOY UNS S30300, TYPE 1

LOCK RING & CONTACT:

BERYLLIUM COPPER PER ASTM B196,

ALLOY No. UNS C17300, TD04

**CRIMP RING:** BRASS PER ASTM B16, ALLOY UNS C36000.

**INSULATOR:** PTFE PER ASTM D1710, TYPE I, GRADE 1, CLASS B

GASKET: SILICONE RUBBER PER A-A-59588,

CLASS 2B, GRADE 50/60

SHRINK TUBING: M23053/4, CLASS 1

FINISH:

BODY.

PRESS CAP. & COUPLING NUT:

PASSIVATED PER AMS-2700.

CONTACT:

GOLD PER ASTM B488, TYPE II, CODE C, CLASS 1.27, OVER NICKEL

PER AMS-QQ-N-290, CLASS 1, .00005" MIN.

NICKEL PER QQ-N-290, CLASS 2. CRIMP RING: FINISH: SEMI-BRIGHT TO DULL

PERFORMANCE:

IMPEDANCE: 50 OHMS

FREQ. RANGE: DC TO 12.4 GHz

VSWR: 1.15 + .02F (F in GHz), 0.5 TO 12.4 GHz OR APPROXIMATELÝ 80% OF THE CUTOFF

FREQUENCY OF THE CABLE WHICHEVER IS LOWER

1.250 MAX[31.75 MAX]	
SHRINK TUBING	

DATE

10/13

APPROVED

STW

MATERIAL: SEE NOTES  FINISH: SEE NOTES  SURFACE AREA: N/A  PROPRIETARY	DIMENSIONS ARE IN INCHES TOLERANCES:  FRACTIONAL: ±1/64 ANGULAR: X° ±1°0′  DECIMAL: X ±.030     .XX ±.010     .XX ±.005  INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994	UNLESS OTHERWISE SPECIFIED  1) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES .005 R. MAX. 4) CHAM. 1ST & LAST THREADS. 5) SURFACE ROUGHNESS 63-MIL-STD-10. 6) DIA.'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN .006 T.I.R. 7) REMOVE ALL BURRS.		UNLESS OTHERWISE SPECIFIED  1) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] 2) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & DOGES . MAX. 4) CHAM. 1ST & LAST THREADS. 5) SURFACE ROUGHNESS 63-MIL-STD-10. 6) DIA:'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R. 7) REMOVE ALL BURRS  THE MOYER ALL BURRS  THE MOYER ALL BURRS  THE MOYER ALL BURRS  THE MOYER ALL BURRS  SWA R/A CRIMPED PL			LUG
THE INFORMATION CONTAINED IN THIS DRAWING		DRAWN:	ELA 10/07/13		R RG303 CABL	<u> </u>	
IS THE SOLE PROPERTY OF SV MICROWAVE, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SV MICROWAVE, INC IS PROHIBITED.	<b>+ + - - - - - - - - - -</b>	CHECKED:	STW 10/07/13	SIZE   CAGE CODE   <b>B</b>   <b>95077</b>	M39012/5	6B3117	
		APPROVED:	STW 10/07/13	SCALE: 6:1		SHEET 1 OF 1	

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: M39012/56B3117