





PDM: Rev:D

STATUS: **Released** ⁴Printed: Dec 23, 2010

PRODUCT NUMBER SEE TABLE I

10087273-00XLF

Α

NOTES CONTINUED:

- 6.) ALL CABLE ASSEMBLIES SHALL BE TESTED 100% FOR CONTINUITY AS DEFINED IN WIRING LIST.
- 7. UNLESS OTHERWISE SPECIFIED ALL CABLE ASSEMBLIES SHALL BE 100% HI-POT TESTED PER PRODUCT SPECIFICATION: GS-12-314.
- 8. OTHER TESTING PERFORMED AS REQUIRED BY PRODUCT SPECIFICATION: GS-12-314.
- (9.) THIS DIMENSION IS A FINISHED PRODUCT LENGTH.
- (10.) LEAD FREE PRODUCTS MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
- CONNECTOR ASSEMBLIES SHOWN ARE FOR REFERENCE ONLY AND MAY NOT SHOW ALL PART DETAIL. REFERENCE CONNECTOR ASSEMBLY DRAWINGS FOR COMPLETE DETAILS.
- 12. PACKAGING PER GLOBAL STANDARD GS-14-1272.
- 13. MATERIALS:

REV F - 2006-04-17

COVERS: ZINC ALLOY, Cu-Ni-Sn PLATED. SHEET METAL COVER: COPPER ALLOY FERRULES: COPPER ALLOY, Ni-Sn PLATED

TERMINAL BLOCK:

- HOUSING: THEMOPLASTIC
- TEMINALS: COPPER ALLOY, FINISH: MIN 0.8um Au ON NI-UNDERLAYER IN CONTACT AREA.
- TRANSITION BOARD: FR4 FIBERGLASS FILLED EPOXY.
- LOCKING SCREW: STAINLESS STEEL
- SCREW STOP: TEFLON
- (14.) MAXIMUM APPLICABLE TORQUE ON LOCKING SCREW = 0.3um



C

yright FC

D

PDM: Rev:D

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

FCI / Amphenol: