



FCIconnect.com

Copyright FCI

D

1		2		3		4		5		6																																																																																																																																																																																																										
 NOTE-1. FOR 14 POSN.HOLE NO.9 IS BLOCKED. ORDERING INFORMATION <table border="1"><tr><td>I</td><td>C</td><td>D</td><td>X</td><td>X</td><td>S</td><td>1</td><td>3</td><td>E</td><td>X</td><td>X</td><td>X</td><td>O</td><td>O</td><td>L</td><td>F</td></tr><tr><td colspan="16">SERIES</td></tr><tr><td colspan="16">NO.OF CONTACTS</td></tr><tr><td colspan="16">14,15,26,44 & 62</td></tr><tr><td colspan="16">TYPE OF CONTACTS</td></tr><tr><td colspan="16">S-SOCKET</td></tr><tr><td colspan="16">TYPE OF TERMINATION</td></tr><tr><td colspan="16">13-ANGLED SPILL PITCH 2.54 USA FOOT PRINT 8.89 USA</td></tr><tr><td colspan="16">HEIGHT OF TERMINATION</td></tr><tr><td colspan="16">E-3.18 US STANDARD</td></tr></table> "This LF product meets European Union Directives and other country regulations as described in GS-22-008" The housing will withstand exposure to 260°C peak temperature for 3.5 seconds in a wave solder application with a 1.6mm minimum thick circuit board. Packaging as per GS-14-920 <table border="1"><thead><tr><th rowspan="2">SIZE</th><th colspan="7">DIMENSIONS</th></tr><tr><th>A±0.38</th><th>B±0.12</th><th>C±0.10</th><th>D^{+0.25}₋₀</th><th>E</th><th>F</th><th>G</th></tr></thead><tbody><tr><td>14/15</td><td>30.81</td><td>24.99</td><td>16.96</td><td>16.21</td><td>7.68</td><td>8.19</td><td>2.285</td></tr><tr><td>26</td><td>39.14</td><td>33.32</td><td>25.18</td><td>24.54</td><td>7.02</td><td>8.01</td><td>2.285</td></tr><tr><td>44</td><td>53.03</td><td>47.04</td><td>39.12</td><td>38.25</td><td>7.01</td><td>8.02</td><td>2.285</td></tr><tr><td>62</td><td>69.32</td><td>63.50</td><td>55.68</td><td>54.71</td><td>7.03</td><td>8.21</td><td>2.41</td></tr></tbody></table> TECHNICAL SPECIFICATIONS MATERIAL SHELL : STEEL TIN/Zinc Cr 3 PLATED. INSULATORS : SELF EXTINGUISHING BLACK POLYESTER UL CLASS 94V0 THE HOUSING WILL WITHSTAND EXPOSURE TO 260-265°C IF WE USE PROTECTIVE ADHESIVE (type Kapton or Teflon) OR PROTECTIVE METALLIC DEVICE CONTACTS : COPPER ALLOY PLATING : GOLD OVER NICKEL SnPb over Ni ACTIVE ZONE : 2 µ MIN.MATTE TIN TOP OVER TERMINATION ZONE : 1.27 µ MIN.NICKEL UNDER PLATE(ON TERMINATION ZONE) FOR LEAD FREE PLATING METAL BRACKET : BRASS,TIN /Zinc Cr3 PLATED. SCREW LOCK : BRASS,TIN /Zinc Cr3 PLATED. HARPOON : BRASS,TIN PLATED. CLINCH NUT : BRASS,TIN /Zinc Cr3 PLATED. ELECTRICAL DATA MAX.CURRENT RATING : 3A TEST VOLTAGE : 1000V RATED VOLTAGE : 300V CONTACT RESISTANCE : <25mΩ SHELL RESISTANCE : <5mΩ INSULATION RESISTANCE : >5000MΩ ENVIRONMENTAL CHARACTERISTICS. OPERATING TEMPERATURE RANGE : -55°C +125°C MECHANICAL CHARACTERISTICS MATING/UNMATING CYCLES (Min.) : 200 MATINGS FOR <0.40µ GOLD PLATING 500 MATINGS FOR >0.75µ GOLD PLATING INSERTION/EXTRACTION FORCE PER CONTACTS : 5 N Max./0.3 N Min.						I	C	D	X	X	S	1	3	E	X	X	X	O	O	L	F	SERIES																NO.OF CONTACTS																14,15,26,44 & 62																TYPE OF CONTACTS																S-SOCKET																TYPE OF TERMINATION																13-ANGLED SPILL PITCH 2.54 USA FOOT PRINT 8.89 USA																HEIGHT OF TERMINATION																E-3.18 US STANDARD																SIZE	DIMENSIONS							A±0.38	B±0.12	C±0.10	D ^{+0.25} ₋₀	E	F	G	14/15	30.81	24.99	16.96	16.21	7.68	8.19	2.285	26	39.14	33.32	25.18	24.54	7.02	8.01	2.285	44	53.03	47.04	39.12	38.25	7.01	8.02	2.285	62	69.32	63.50	55.68	54.71	7.03	8.21	2.41
						I	C	D	X	X	S	1	3	E	X	X	X	O	O	L	F																																																																																																																																																																																															
						SERIES																																																																																																																																																																																																														
						NO.OF CONTACTS																																																																																																																																																																																																														
						14,15,26,44 & 62																																																																																																																																																																																																														
TYPE OF CONTACTS																																																																																																																																																																																																																				
S-SOCKET																																																																																																																																																																																																																				
TYPE OF TERMINATION																																																																																																																																																																																																																				
13-ANGLED SPILL PITCH 2.54 USA FOOT PRINT 8.89 USA																																																																																																																																																																																																																				
HEIGHT OF TERMINATION																																																																																																																																																																																																																				
E-3.18 US STANDARD																																																																																																																																																																																																																				
SIZE	DIMENSIONS																																																																																																																																																																																																																			
	A±0.38	B±0.12	C±0.10	D ^{+0.25} ₋₀	E	F	G																																																																																																																																																																																																													
14/15	30.81	24.99	16.96	16.21	7.68	8.19	2.285																																																																																																																																																																																																													
26	39.14	33.32	25.18	24.54	7.02	8.01	2.285																																																																																																																																																																																																													
44	53.03	47.04	39.12	38.25	7.01	8.02	2.285																																																																																																																																																																																																													
62	69.32	63.50	55.68	54.71	7.03	8.21	2.41																																																																																																																																																																																																													

form: A3

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[ICD26S13E6GV09LF](#) [ICD26S13E4PA00LF](#) [ICD26S13E6PA00LF](#) [ICD44S13E6UX00LF](#) [ICD44S13E6PX00LF](#)