









THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2012/10/22	Ruru	LC20-02RMFS-SS8001 To LC20-02PMFS-SN8001
B	LE31650229	2016/05/04	Vicky	Update Note



- Note:
- * $\varnothing$ Important Dimension.
 - * Waterproof Rate: IP68
IP68: 1M depth of water in 24 Hrs.
(防水等級: IP68)
IP68: 水深一米測試 24 小時
 - * Shell: Zinc Alloy#3, Ni Plated, Silver.
 - * Insulation: Nylon, Black
 - * Female Pin: Copper Alloy, Silver Plated
 - * Gasket: Silicone, Gray
 - * Recommended Panel Thickness 5.0mm(Max).

UNIT: mm		TITLE		Amphenol LTW		ITEM NO	DRAWN BY	DATE
TOLERANCE		PANEL NUT 2PIN M CONN F PIN		安費諾亮泰企業股份有限公司		LC20-02PMFS-SN8001	Vicky	2016-05-04
.X	±0.25	SCALE	1:1	SIZE	A4	DWG NO	CHECKED BY	DATE
.XX	±0.1	REV.	B	WC-REV.	A.2	LC20-02PMFS-SN8001	Rita	2016-05-04
.XXX	±0.05	QC: Inspection item				CUSTOMER	APPROVED BY	DATE
ANGLES	±1°					ALTW	Lisa	2016-05-04

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[LC20-02PMFS-SN8001](#)