









SECTION A-A

REVISIONS										
REV	ECO	DESCRIPTION	DATE	BY	APPR					
B1	-	RELEASE NEW DWG FORMAT	05/10/14	DRACK						
B2	-	ADDED PIN NUMBERS	08DEC15	MRF						

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

INSULATION INSERT:PBT,UL94 V0

SEAL: VITON

HOUSING BODY: ZINC DIE CAST, NICKEL PLATED COUPLING NUT: COPPER ALLOY, NICKEL PLATED

2. SPECIFICATIONS:

2.1 CURRENT RATING: SIGNAL: 1 AMPS

POWER: 18 AMPS

QUAD ELEMENT:0.5 AMPS

2.2 VOLTAGE RATING: SIGNAL: 850V AC/DC

POWER: 850V AC/DC

QUAD ELEMENT: 30V AC/DC 2.3 OPERATING TEMPERATURE: -20°C TO +130°C

2.4 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2

MILLIAMPS CURRENT LEAKAGE @ SIGNAL: 1500 VOLTS AC.

POWER: 6000 VOLTS AC.

QUAD ELEMENT: 500 VOLTS AC.

TITLE: RECEPTACLE, STRAIGHT, PANEL MOUNT, HYBRID, THREADED

DWG NO:

MB1YSN8H00

* **B2** SH:

2.5 DEGREE OF PROTECTION: IP67 (MATED CONDITION)

2.6 DEGREE OF POLLUTION: 3 PER UL840

2.7 OVERVOLTAGE CATEGORY: III PER UL840

2.8 MATING CYCLE DURABILITY: >500 CYCLES

2.9 RoHS COMPLIANT

3. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

SEE PART NUMBER										
	0==:/::									
QUANTITY	CHART PART NUMBER		DESCRIPTION			ITEM				
MATERIALS LIST										
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 2 PL DEC ±0.15 3) Note reference = MATERIAL SPECIFICATIONS: PROCESS SPECIFICATIONS: NEXT ASS'Y:		SIGNATURE	S DATE	Amphenol						
		Drack Drack	05/10/14							
		CHECKED:		Sine Systems - www.amphenol-sine.com						
		ENGINEER:		44724 Morley Drive Clinton Township, MI 48036						
		APPROVAL:				Cilitari Township, Wii 40000				
		CUSTOMER:		RECP, ST, PANEL MOUNT, HYBRID, THRD'D						
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION, NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL								
				B	C-	MB1YSN8H00	B2			
				SCALE: N	ONE	SHEET 1 OF	1			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: MB1YSN8H00