

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

1	2	3	4	5	6	7	8	
F				REV C D E	ECN NO. LEN-960019~22 LEN-9B0075~78 LEN1540187~190	DATE 2009/03/12 2009/10/21 2015/03/18	SIGN Li Xiu Zhi Li Xiu Zhi Ruru	DESCRIPTION Change SR Change SR Change Logo
E								
D								
C								
B								
A								

Shell	Drain	地線	25	Pink/Black	粉/黑	
12	Light Green	淺綠	24	Grey/Black	灰/黑	
11	Pink	粉	23	Green/Black	綠/黑	
10	White	白	22	Yellow/Black	黃/黑	
9	Grey	灰	21	Orange/Black	橙/黑	
8	Purple	紫	20	Red/Black	紅/黑	
7	Blue	藍	19	Purple/White	紫/白	
6	Green	綠	18	Blue/White	藍/白	
5	Yellow	黃	17	Green/White	綠/白	
4	Orange	橙	16	Orange/White	橙/白	
3	Red	紅	15	Red/White	紅/白	
2	Brown	棕	14	Brown/White	棕/白	
1	Black	黑	13	Black/White	黑/白	
Conn.	Wire Color	Conn.	Wire Color			
Pin Out						

UNIT:mm		TITLE	D-SUB Conn. Molded Screw		
		DB25Pin M Conn. M Pin			
TOLERANCE $\pm 0.5$ mm		SCALE	Free	SHEET	1 OF 1
		REV.	E	SIZE	A4
		<b>QC : Inspection Item</b>			

**Amphenol LTW**  
安費諾亮泰企業股份有限公司

Note:  
 \* QC Important Dimension To Check.  
 \* Waterproof Rate: IP67  
 \* Connector: D-SUB 25 Pin Male  
 \* Cable: UL2464 24AWG\*25C+Drain+Al/My (UV Resistant)OD=9.0mm, Black  
 \* Cable Length Tolerance: 01M:±40mm  
 02M~05M:±60mm  
 06M~10M:±100mm  
 11M~30M:±200mm  
 31M~99M:±500mm

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[SDB-25AMMM-SL7A03](#)