SP14M2G5Sμ"GOLD PLATING OVER NICKEL.SP14M2G1010μ"GOLD PLATING OVER NICKEL.SP14M2G1515μ"GOLD PLATING OVER NICKEL.SP14M2G3030μ"GOLD PLATING OVER NICKEL.		CONTACT ORIENTATION ON ROLL(3000PCS/COIL) NOTES : (UNLESS OTHERWISE SPECIFIED) 1. MATERIAL : 1.1. CONTACT BODY : COPPER ALLOY. 1.2. OUTER SPRING : STAINLESS STEEL. 2. SPECIFICATIONS : 2.1 CURRENT RATING : 13A MAX. 2.2 TERMINATION TYPE : CRIMPING. 2.3 WIRE RANGE : 14~16AWG. 2.4 WIRE INSULATION DIA(MAX) : Ø3.2mm. 3. ROHS COMPLIANT. 4. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY. 5. AVAILABLE TOOLS : 5.1 HAND CRIMPER : MFX-3957. 5.3 EXTRACTION TOOL : QXRT16.		
		27.7 REF 9.1 9.1 9.1 9.1 9.1 9.1 9.1 9.1 9.1 9.1	8.9	
Productions Production Production 1 Production Product Product 1 Production Product Product 1 Product Product Product <td>QUANTITY PART NUMBER DESCRIPTION MATERIALS LIST</td> <td>SECTION AA</td> <td>- RELEASED DRAWING Jul-16-18</td> <td>BY</td>	QUANTITY PART NUMBER DESCRIPTION MATERIALS LIST	SECTION AA	- RELEASED DRAWING Jul-16-18	BY

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: SP14M2G10