







NOTES:

- 1. PERFORMANCE:
 - A) MEETS PERFORMANCE AND ENVIRONMENTAL REQUIREMENTS OF MIL-T-81714/1
 - B) MODULES ARE TO BE MOUNTED INTO RACK ASSEMBLY M81714/5 OR/16 OR COMMERCIAL EQUIVALENT.
 - C) DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS AT SEA LEVEL, 200 VRMS AT 100,000 FEET.
 - D) OPERATING TEMPERATURE: -65 C TO 200 C.
 - E) CURENT RATING: 5 AMPS
- F) VIBRATION AND SHOCK: MIL-T-81714 PARAGRAPH 3.5.5 AND 3.5.8 2. MATERIALS:
 - A) HOUSING POLYETHERIMIDE, COLOR: BLACK.
 - B) GROMMET SILICONE ELASTOMER, COLOR: BLUE
 - C) INTERNAL CONTACTS COPPER ALLOY, GOLD PLATED
 - D) CONTACT RETAINERS STAINLESS STEEL.

1000 D (1)		SUPPLIED					MARKING	
APCD P/N		PINS			PLUGS	APCD QPL NO.	MIL. NO	CLA
	QTY.	MIL. P/N	APCD P/N	QTY.	APCD P/N			
TJM122608						TJM122708 M81714/1-	M81714/1-DE1	n
TJM122708	11	M39029/1-100	CNP068000	2	CNA032401	1 3141122 708	WIGIT ITT FDEI	ט

Δ	PROJECTION	TOLERANCES	DIMENSIONS		
^		.XX ±0.01	ANSI Y14.5M		
DRWN		.XXX \pm 0.005 ANGLES \pm 2.0 $^{\circ}$	UNITS: INCHES		
Α.		ANGLES ±2.0	Pro/E FILE		
ENGR	NT CONTAINS	ORIGINAL			
R.	FORMATION WHICH				
APPD	NTIAL PROPERTY				

OF AMPHENOL PCD INC., PEABODY, MA

Amphenol Pcd

SPECIFICATION DRAWING

DRWN

A. SWEEZEY 03/09/06

ENGR

R. SWAINE

rade TZ

03/09/06 SZ 03/01/06 B DWG NO. 4-(3-06 CODE: 58982

TITLE

TERMINAL JUNCTION

MODULE

SZ 22 FEEDBACK, DE1

TJM122608 -

SCALE: 3:1 SHEET 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

TJM122708 TJM122608