F	1 2	3	4	5 Rev. ECN NO. A Initial Rel	6 ease 2009/04/15	7 Doreen Change R	8 2EV.02 to REV.A EV.02 to REV.A SUBJECT TO
E	Cable (2)					/8"-16 UN	DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amplemol LTW. DISCLOSURE TO THIRD PARTY C. DEPT. DENTIAL 99.05.04 UED 4 ated 0+AC) .2mm
C	UMN-	-05AMMM-SL8000 (1) : Black CONFIDENTIAL 2009.04.15 R&D DEPT.	<u>01</u> :0	<u>Conn.</u> <u>X</u> 1~99Meters 1Meter 2Meters	Note: * @CImportant * Waterproof R * Connector: B * Nut: ZN-ZDC	Dimension. ate: IP68	D A PROPERTY OF Amphenol LTW. DISCLOSURE
Β	Pin Assignments Front View	Blue 藍5White 白4Black 黑3Red 紅2Drain1Wire ColorConnPin Out	: <u>99</u> :99 Cable Length(L):0		* Cable: (18#+ +Drain+AL.My * Cable Length	06M~ 11M~ 31M~	±40mm 表 05M:±60mm る 10M:±100mm 用 30M:±200mm 各 99M:±500mm 日 099M:±500mm
		NMEA Mini onn M Pin For Cable ree <sup>SHEET</sup> 1 OF 1 <sup>SIZE</sup> A4 @C :Inspection Item 3	Amphenol 安費諾亮泰企業股份	I IMN-C	5AMMM-SL8CXX	RAWN BY Doreen SHECKED BY Kathy PPROVED BY Yitung 7	DATE 2009/04/17 DATE 2009/04/17 DATE 2009/04/27 8 FMWI0702-01-01A2

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: UMN-05AMMM-SL8C40