NOTES:

1. MATERIALS AND FINISHES:

BODY - BRASS, GOLD PLATING

CONTACT - BERYLLIUM COPPER, GOLD PLATING

INSULATOR - PTFE

ELECTRICAL:

A. IMPEDANCE: 50 OHM

ø3.5

B. FREQUENCY RANGE: DC 0-6 GHz C. DIELECTRIC WITHSTANDING VOLTAGE: 500 VRMS, MIN.


MECHANICAL:

A. DURABILITY: 500 CYCLES MIN.

B. TEMPERATURE RANGE: - 65°C to +165°C

4. PACKAGING:

A. PACKAGE CONNECTOR IN TAPE AND REEL, QTY OF 750 PCS



Ø0.7

- 0.1 $^{+0}_{-0.1}$ 

- 5.21 -

 $\oplus$ 


A SEE SHEET 1

B SEE SHEET 1

C SEE SHEET 1

D ADD NOTE 4\RD-DM10040701T1

THIRD ANGLE PROJ.



REVISIONS

APPR

SH

SH

SH

J.C

ECO

47924

48059

49948

DATE

05-Mar-03

11-Aug-08

30-Apr-09

15-Apr-10

03-Mar-14

DESCRIPTION

4.45 WAS 4.5,5.21 WAS 5.26\RD-DM14012101J8

RECOMMENDED MOUNTING PATTERN

## **CUSTOMER OUTLINE DRAWING**

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: 0.5 - 6mm 6 - 30mm 30 - 120mm ANGLES	MATERIAL	drawn  J.CHEN	DATE	TITLE			Amphenol RF
±0.1mm ±0.2mm ± 0.3mm ±1*  NOTICE — These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are	REFERENCE	U.CHEIN ENGINEER	26-Mar-14	WWOX SONTAGE WOOTEN GAGE			Danbury CT USA, Tainan Taiwan, Shenzhen China
		KEN	DATE 05-Mar-03				www.amphenolrf.com
		APPROVED	DATE				DRAWING NO. MMCX6251N3-3GT30G-50
		SCOTT	28-Mar-14	SCALE: 12/1	SHEET	1 OF 1	ITEM NO
		CAD FILE	ZO WIGH 14	DWG SIZE	CODE ID	REV	096251AAG56GE5F
product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.		F:\DWG\MMCX\6251N3\50\3GT30G-ESZ		В	74868	E	PART NO. 908-22116

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

<u>Amphenol</u>: 908-22116