

# 1.00mm Pitch FFC/FPC – F51L Series

## RIGHT ANGLE ZIF FLEX CONNECTOR

F51L series is a 1.00mm pitch right angle ZIF flex connector with front flip locking mechanism, double contacts and surface mount termination. This connector features a height of 2.55mm and comes in 4 to 30 contacts. This series features a cable thickness of 0.30mm and provide enhanced durability of 30 mating cycles. The connectors come with a robust design and prevent solder and flux wicking. These are ideal for automotive, data, industrial, communication, consumer and medical applications.

- Easy to operate and strong FFC/FPC retention makes it vibration-proof
- Double contact points provide enhanced contact stability
- Ensures high solderability and high durability



### FEATURES

- ZIF (Zero Insertion Force) mechanism
- Front flip locking function
- Double contact points
- Design against solder and flux wicking
- High temperature thermoplastic housing
- 4 to 30 contacts available
- Lead and halogen-free

### BENEFITS

- Absence of frictional mating wear resulting in high mating cycle life
- Easy to operate and strong FFC/FPC retention makes it vibration-proof
- Provides enhanced contact stability
- Ensures high solderability
- Wide operating temperature range of  $-40^{\circ}\text{C}$  to  $+105^{\circ}\text{C}$
- Comprehensive range to satisfy different customer requirements
- Meets environmental, health and safety requirements

## TECHNICAL INFORMATION

### MATERIAL

- Housing: LCP, natural color (UL94V-0)
- Actuator: PA9T, black color (UL94V-0)
- Contact : Phosphor bronze, T=0.20mm
- Stator: Brass, T=0.20mm
- MYLAR: T=0.10mm, thermostable, yellow color

### MECHANICAL PERFORMANCE

- FFC/FPC Retention Force: 40~70gf/pin
- Terminal Retention Force: 100gf/terminal min.
- Stator Plate Retention Force: 100gf/plate min.
- Durability: 30 mating cycles

### ELECTRICAL PERFORMANCE

- Voltage Rating: 50V AC/DC
- Current Rating: 0.5A
- Contact Resistance: 30MΩ max.
- Insulation Resistance: 500MΩ min.
- Dielectric Withstanding Voltage: No short or breakdown after 500V AC, 2mA, 1min.

### PACKAGING

- Tape & Reel

### APPROVALS AND CERTIFICATIONS

- UL file number E41797
- RoHS compliant

### SPECIFICATION

- Aorora Product Specification: IS.EQC.039

### ENVIRONMENTAL

- Operating Temperature Range: -40°C to +105°C

### TARGET MARKETS/APPLICATIONS



Car Multimedia  
Car Navigation  
Dashboard  
PND



Base Station  
Power  
Switches



Notebook  
Tablets  
Wearables  
Gaming  
DSC  
LCD & PDP TV



Router  
Server  
ODD  
HDD




Sensing element  
Monitoring camera  
Human Machine Interface  
Industrial PC  
Robotics



Ultrasonic  
Patient Monitor  
MRI  
CT  
Infusion Pump

## PART NUMBER SELECTOR



AOR0RAF51L0719EA4

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Amphenol:

[F51L-1A7H1-11004](#) [F51L-1A7H1-11006](#) [F51L-1A7H1-11008](#) [F51L-1A7H1-11010](#) [F51L-1A7H1-11012](#) [F51L-1A7H1-11013](#) [F51L-1A7H1-11028](#) [F51L-1A7H1-11014](#) [F51L-1A7H1-11016](#) [F51L-1A7H1-11018](#) [F51L-1A7H1-11020](#) [F51L-1A7H1-11022](#) [F51L-1A7H1-11024](#)