

## CFP2

Amphenol ICC's CFP2 series offers a 104 position, 0.6mm pitch connector designed to be compatible with 100Gb/s Form Factor Pluggable (CFP) Multi-Source Agreement for Ethernet and other applications. It is used in multi-hundred Gb/s systems and is comprised of insert molding assemblies for top contacts and press-fit cage assemblies. Rated for 25Gb/s per channel with resonance dampening for improved signal integrity, CFP2 has up to 60% lower power consumption versus CFP. An optional riding heat sink ensures proper thermal dissipation. Compatible with IEEE and ITU-T applications, the CFP2 footprint is compliant with other industry suppliers.



### TARGET MARKETS



## TECHNICAL INFORMATION

### MATERIAL

- Housing: Black color, Glass reinforced, Lead Free Solder Reflow Process Compatible Thermo Plastic
- Contacts Base Material: Phosphor Bronze
- Plating Solder Tails: Matte tin
- Plating Mating Area: Gold
- Resonance Dampening Feature: Conductive Polymer

### MECHANICAL PERFORMANCE

- Durability: 200 mating cycles
- Mating Force: 80 N max.
- Contact Normal Force: 40 grams
- PCB Thickness (Cage): 3.00 mm (0.118 in.)
- Unmating Force (Cage): 50 N
- Insertion Force to PCB (Cage): 2 port – 2000N max.

### ELECTRICAL PERFORMANCE

- Operating Voltage: 3.3 V DC per contact
- Operating Current (per power pin): 0.5A maximum (Class 4 or lower) / 1.25A maximum (Class 5 and 6)
  - Please contact the manufacturer for specific requirements over 0.5A per pin
- Operating Current (per signal pin): 0.5A maximum
- Differential Impedance: 100Ω +/- 10Ω

### ENVIRONMENTAL

- Operating and (Storage) Temperature: -40°C to +85°C
- RoHS & Halogen-Free

### TOOLING INFORMATION

- Configurations: 1X1, 1X2

### TARGET MARKETS/APPLICATIONS




Metro Area Networks




Carrier Networks and Data Centers  
Large Data Center Campus Connectivity

PART NUMBER SELECTOR

CFP2 Connector



CFP2 Cage



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Amphenol:

[U99-B104-200T](#) [U98-B121-1001](#) [U98-B221-1001](#) [U56B1042001](#) [U98B2411D01](#) [U98-B111-10B1](#) [U98B11110A1](#)  
[U98B1111001](#) [U98B1211D01](#) [U98B1221DC1](#) [U98B2111001](#)