

SHORT BODY PCMCIA CONNECTORS

OVERVIEW

FCI's short body PCMCIA header extends personal computer memory card application to set-top boxes and digital displays. Its short body design helps achieve excellent signal transmission. The lightweight design includes EMI and grounding options while saving valuable board real restate.

Like all FCI's PCMCIA products, the short body version complies to PCMCIA and RoHS standards.



FEATURES & BENEFITS

- Enhanced metal cover enables EMI/ESD/grounding
- Customized standoffs allowed height adjustments
- · Space saving and lightweight
- Meets both 5.0 and 3.3V requirements
- · Non-eject style for static card designs

TARGET MARKETS/APPLICATIONS

- Consumer
 - · Set-top box
 - · LCD TV

TECHNICAL INFORMATION

MATERIALS

- · Contact: Copper alloy
- · Contact area: Gold over nickel
- · Solder tail area: Pure tin over nickel
- · Cover: Metal steel
- · Housing: High temperature thermal plastics

ELECTRICAL PERFORMANCE

- Electrical withstanding voltage: Current leakage 1mA max. after 500V AC for 60 second
- Insulation resistance: Initially 1000M $\!\Omega$ min. , after test 100M $\!\Omega$ min.
- Contact resistance: Initially $40m\Omega$ max. $20m\Omega$ changes max. after test

ENVIRONMENTAL

• Operating temperature range: -55°C to +85°C environmental tests

PART NUMBERS

Description	Part Numbers
3.3V metal cover type	10067972 series
5.0V metal cover type	10074595 series
5.0V full plastic type	92150 series

MECHANICAL PERFORMANCE

- Max. insertion force: 39.2 N
 Min. withdrawal force: 6.67 N
- Durability: 10,000 cycles for 68 contact pins
- Vibration: Contact resistance $20m\Omega$ changes from initial, no more than 100 second discontinuity

SPECIFICATIONS

• 110 - 263 product specification

APPROVALS AND CERTIFICATIONS

- UL & RoHS
- · PMCIA compliance

PACKAGING

Tray

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

FCI / Amphenol:

83808-20000S 83808-20110S 83808-22111S 91113-12CA 83818-20000 83818-20111 92789-040HLF 92140-500LF 95620-120CALF 92140-002LF 92140-010LF 92140-000LF 95547-020CALF 95547-655CALF 95547-155CALF 95547-050CALF 95548-0043LF 95548-0500LF 95548-5050LF 95548-5522LF 9562-350CALF 95620-002CALF 95620-050CALF 95620-100CALF 95620-150CALF 95620-602CALF 95620-620CALF 95635-200CALF 95705-040LF 95705-500LF 95706-040LF 95706-040LF 95706-510LF 95706-520LF 83808-10000S 83808-10010 83808-1010 83808-2010 83808-2010 83808-2010 83808-2010 83808-2010 83808-2010 83808-2010 83808-2010 83808-2010 83808-2010 83808-2010 83808-2011 83818-2001 83808-2011 83808-2010 83