


SIGN	DATE	DESCRIPTION	APPROVER
△	04/07'10	Add the 2P mark	RUNNER
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			




Dimension

DIM A	$N \times 5.08 + 0.62$
DIM B	$(N-1) \times 5.08$

N=Number of poles

POLES	TOL
2p-6p	± 0.15
7p-12p	± 0.25
13p-16p	± 0.35
17p-24p	± 0.40



Material



- Item a Terminal body:Thermoplastic (UL94V-0)
- Item b Terminal body:Thermoplastic (UL94V-0)
- Item c Terminal lever:Thermoplastic (UL94V-0)
- Item d Wire guard:Stainless Steel
- Item e Female contact:PhBz (CuSn) Tin plated
- Item f Wigh flange screw:Steel Zinc plating M2.5 solt "+/-" type

Electrical cULus



- Voltage rating:300V
- Current rating:10A
- Solid wire(AWG):12-26
- Stranded wire(AWG):12-26
- Wire strip length:9-10mm
- Withstanding Voltage:1.6KV
- Operating temperature:-40°C to +115°C
- Safety Approval: cULus

H4 xx 50 x D xxxx G

02 2 CONTACTS	0 Black	0000 Standard @ Logo	RoHS
03 3 CONTACTS	4 Orange	000A Standard ANY Logo	Pb<40,000ppm
... ..	5 Green	Any special item by	
24 24 CONTACTS	6 Blue	customer request,	
	8 Grey	please contact sales	
		department.	



SECTION A-A



ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	H4 5.08 Series hook on back side (With flange)			
PART NO.	H4xx50xDxxxxG		DWG NO.	8H40204
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.
		Runner 2010.04.07	Tony 2009.03.12	
		SHEET: 01/01		UNIT: mm
				SCALE: NONE
				Tolerance
				X. ± 0.50
				X.X ± 0.30
				X.XX ± 0.10
				X* $\pm 1^*$

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

<u>H402505D0000G</u>	<u>H403505D0000G</u>	<u>H404505D0000G</u>	<u>H405505D0000G</u>	<u>H406505D0000G</u>	<u>H407505D0000G</u>
<u>H408505D0000G</u>	<u>H409505D0000G</u>	<u>H410505D0000G</u>	<u>H411505D0000G</u>	<u>H412505D0000G</u>	<u>H413505D0000G</u>
<u>H414505D0000G</u>	<u>H415505D0000G</u>	<u>H416505D0000G</u>	<u>H417505D0000G</u>	<u>H418505D0000G</u>	<u>H419505D0000G</u>
<u>H420505D0000G</u>	<u>H421505D0000G</u>	<u>H422505D0000G</u>	<u>H423505D0000G</u>	<u>H424505D0000G</u>	