





Note:

- I. Material:thermo plastic,ul94 v-0
- 2. Bulkhead thickness range: 0.79-2.54
- 3. Color:black

Pro/E File - REV C - 2009-06-09

- 4. Applicable components Applicable power crimp contact: 10132418-****LF Applicable contact secondary lock:10073097-DGC001LF Applicable signal contact 76347-DGC302LF Applicable latch 10066441-DGC001LF for STR version
- 5. Product Spec: GS-12-474
- 6. Application Spec: GS-20-0445
- 7. The part is been sold as loose piece and fci guarantees is the part in compliance with this customer drawing statement. The product spec for cable assemly can be only as the reference document because the testing and spec is based on using fci raw cable and cable asseymble. If the raw cable and cable assembly is outside suppliers sourced by cusotmers, customers or cable assembly suppliers should be fully responsible for the cable assy quality.

spec ref	*			dr Yo	ong Zhang		2016/01/26	proj	ection		111	s i z e	scale	
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng Yo	e n g Yong Zhang		2016/01/28				MM		A 4 I:I	
				chr -		-				-		-		
				appr Gu	uo-Feng Jin		2016/01/28	product	family		PWRBLADE	rel level	Released	
surface 🗸	linear	0 . X	±0.5	CC:	~ :	υ Q C	ı LAD	DM			0 U		rev	
		0 . X X	±0.25			= 8S + 10P PM		L IAI			D 1006	66440-DG	C0259LF	259LF
		0.XXX	±0.10			+ Pwr	PwrBlade Cable				» p			Α
	angular	0°	±2°	www.fo	ci.com	cat. no	,	*	Pr	oduct -	Customer	r Drw	sheet 2 of	2

В

PDS: Rev:A

STATUS:Released

Printed: Jan 28, 2016

В

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

FCI / Amphenol: 10066440-DGC0259LF