




PART NUMBER	"L" DIM
10091790-001LF	.250" ^{+.000} _{-.020}
10091790-002LF	.375" ^{+.000} _{-.020}
10091790-003LF	.500" ^{+.000} _{-.020}
10091790-004LF	.625" ^{+.000} _{-.020}



SQUARE CONE LOCK WASHER

2-56 UNC-2A THREAD

NOTES:

1. MATERIAL: SCREW: 18-8 STAINLESS STEEL PER ASTM F593
WASHER: 410 STAINLESS STEEL

2. DRIVE SIZE: #1 PHILLIPS

spec ref	-	dr	Jim Swain	2010/01/26	projection	INCH	size	A3	scale	10:1
tolerance std	ASME Y14.5	eng	Jim Swain	2011/05/19	chr	-	ecn no	-	rel level	Released
surface	✓	appr	Steve Minich	2011/05/19	product family	-	rel level	Released	rev	A
linear	0.X	±	-	FCI	SCREW, SEMS, PAN-HEAD, PHILLIPS, #2-56 THREADED	dwg no	10091790	cat. no.	SEE P/N TABLE	Product - Customer Drw
angular	0°	±	-	www.fci.com	Product - Customer Drw	sheet 1 of 1				

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[10091790-004LF](#) [10091790-003LF](#) [10091790-002LF](#) [10091790-001LF](#)