




ExpressPort® QSFP+

Product Description

The ExpressPort® QSFP+ interconnect system is comprised of a 38 position 0.8mm pitch SMT connector, and a press-fit cage. With four channels of data in one pluggable, the system interface is capable of transferring data up to 28 Gbps/Channel, and replacing up to 4 standard SFP+ receptacles. These features result in greater port density and overall cost savings over traditional SFP+ products. Supporting standards include, Gigabit Ethernet, InfiniBand, and SON-ET/SDH with different data rate options. ExpressPort® QSFP+ includes cages in single, ganged and stacked configurations with multiple heat sink options supporting various thermal requirements and port status with light pipes options.

Applications		SFF Supported Standards	
Data Servers	SAN, NIC cards	ExpressPort QSFP+	
Router/Switches	HBA'S	Connector SFF-8682	
Hubs		Cage SFF-8683	
Product Specifications - ExpressPort® QSFP+			
CONNECTOR		CAGE	
Materials Specifications			
Housing	Black color, Glass reinfor ced , Lead Free Solder Reflow Process Compatible Thermo Plastic	PCB Thickness	1.44 mm MIN for single mounted. (1xN)
Contacts Base Material	Phosphor Bronze	Belly to Belly	2.85 mm MIN for 1xN. 1.57 mm MIN for 2xN.
Contact Normal Force	50 grams min.		
Plating Solder Tails	Matte tin		
Plating Mating Area	Gold		
Resonance Dampening Feature	Conductive Polymer		
Operating & Storage Temperature	-40° to +85° C		
Electrical Specifications			
Operating Voltage	30 VDC per contact		
Operating Current	0.5 A per contact		
Differential Impedance	100 Ω +/-10 Ω		
Mechanical Specifications			
Mating Force	40 N Maximum	Unmating Force	30 N Maximum
Durability	250 mating cycles	Insertion Force to PCB	780 N for 1 port 1000 N for 2 Ports 1700 N for 4 Ports 2400 N for 6 Ports
Options			
Packaging	Tape and Reel	Packaging	Tray
EMI Options	Gasket, Spring Fingers		
Cage Mounting	Behind Bezel, Thru Bezel, Hybrid		
Configurations	1XN (N=1,2,3,4,6) 2XN (N=1,2,3)		
Environmental Specifications			
RoHS	Yes		
Halogen Free	Yes		
Flammability Rating	UL 94V-0		





Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[U90-1101-611A-BP](#) [U90-1101-7000-BP](#) [U90-A101-1001](#)