



SIGN	DATE	DESCRIPTION	APPROVER
△	3/6'07	增加溝槽尺寸規範	Marvin
△	4/7'09	Voltage,wirerange,torque,operating temperature safety approval are changed	Jody
△	4/7'09	Name changed	Jody
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

#### Material

- Item① Terminal body(metal housing): Steel stamped clamp
- Item② Terminal screw: Steel Zinc plating "+/-" slot type
- Item③ Wire guard: Stainless steel
- Item④ Insulator (housing): Thermoplastic (UL94V-0)

#### Electrical cULus

- △ ● Voltage rating: 300VAC
- Current rating: 57A
- Wire range:
- △ ● Solid wire(AWG): 6-22
- △ ● Stranded wire(AWG): 6-22
- △ ● Torque: 13 Lb-In
- Screw: M4
- Wire strip length: 8-9mm
- △ ● Withstanding Voltage: 1.6KV
- △ ● Operating temperature: -40°C to +115°C
- △ ● Safety Approval: cULus

$$A=(N-1) \times 12.5+10.5$$
$$B=(N-1) \times 12.5$$

N=NUMBER OF POLES

POLES	DIM A	DIM B	TOL
2P	23.0	12.5	+0.40 -0.40
3P	35.5	25.0	
4P	48.0	37.5	
5P	60.5	50.0	
6P	73.0	62.5	

EN xx 04 x 0 xxxx G

02 2 Poles    0 Black    000 0 @ logo    G: Pb<40,000ppm  
03 3 Poles    4 Yellow    000 A ANY logo  
...    ...    5 Green    Any special item by  
06 6 Poles    8 Grey    customer request,  
please contact sales  
department.

# ANYTEK

## CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	EN-12.5 Series (2~6P) △						
PART NO.	ENxx04x00000G			DWG NO.	8EN0001		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			
		JODY 2009.4.7	JODY 2009.4.7		Tolerance		
					X.	±0.50	
					X.X	±0.30	
					X.XX	±0.10	
					X°	±1°	
				SHEET: 01/01	UNIT: mm	SCALE: NONE	REV.: D

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[EN0204800000G](#) [EN0304800000G](#) [EN0404800000G](#) [EN0504800000G](#) [EN0604800000G](#) [EN0604000000G](#)  
[EN0404000000G](#)