





3	PHOSPHOR BRONZE	TIN-COPPER PLATED 1μ m min UNDER PLATING:NICKEL PLATED 0.5μ m min					
2	BRASS	TIN-COPPER PLATED 1μ m min UNDER PLATING:NICKEL PLATED 0.5μ m min	5	POLYESTER	CLEAR(COVER TAPE)		
		4	A-PET	CLEAR (EMBOSSED CARRIER TAPE)			
1	POLYAMIDE	BEIGE, UL94V-0					
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS		
CODE NO.(OLD) CL			DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
			Fr. Matsuki 03. 3. 5	J. Denkouya 03. 3. 7	T. Miyazaki 03. 03. 25	T. Miyazaki 03. 03. 25	. .
			DRAWING NO. EDC3-160309-17		PART NO. DF14A-*P-1.25H(26)		
SCALE 5 : 1			CODE NO. CL538-				
UNITS mm							
			 HIROSE ELECTRIC CO., LTD				
							

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					.	△					.
△					.	△					.
△					.	△					.




PART NO.	CONTACTS	F	G	H	J	K
DF14A- 2P-1.25H(26)	2	7.5	-	16	7.85	16.4
DF14A- 3P-1.25H(26)	3	7.5	-	16	9.1	16.4
DF14A- 4P-1.25H(26)	4	11.5	-	24	10.35	24.4
DF14A- 5P-1.25H(26)	5	11.5	-	24	11.6	24.4
DF14A- 6P-1.25H(26)	6	11.5	-	24	12.85	24.4
DF14A- 7P-1.25H(26)	7	11.5	-	24	14.1	24.4
DF14A- 8P-1.25H(26)	8	11.5	-	24	15.35	24.4
DF14A- 9P-1.25H(26)	9	11.5	-	24	16.6	24.4
DF14A-10P-1.25H(26)	10	11.5	-	24	17.85	24.4
DF14A-15P-1.25H(26)	15	20.2	40.4	44	24.1	44.4
DF14A-20P-1.25H(26)	20	20.2	40.4	44	30.35	44.4
DF14A-25P-1.25H(26)	25	26.2	52.4	56	36.6	56.4
DF14A-30P-1.25H(26)	30	26.2	52.4	56	42.85	56.4



SUPPLIER
 QUANTITY
 PART NO.
 CODE NO.
 DATE OF MANUFACTURED
DETAIL OF PART NO. LABEL

生産月日	年 月 日
CLコード	538-****-*-26
品名	DF14A-*P-1.25H(26)
納入数量	1000個
納入者	ヒロセ電機株式会社

NO.		MATERIAL		FINISH, REMARKS		NO.		MATERIAL		FINISH, REMARKS			
CODE NO. (OLD) CL				DRAWN		DESIGNED		CHECKED		APPROVED		RELEASED	
				F. Matsuki 03.3.5		I. Dompouya 03.3.7		T. Miyazaki 03.03.25		T. Miyazaki 03.03.25			
		DRAWING NO.				PART NO.							
SCALE		EDC3-160309-17				DF14A-*P-1.25H(26)							
FREE		 HIROSE ELECTRIC CO., LTD				CODE NO.							
UNITS						CL538-		2/					
mm													

NOTE 4 1 REEL : 1000 CONNECTORS
5 AT THE BEGINING OF THE REEL , 30 COMPONECTS SHALL BE EMPTY .
6 AT THE END OF THE REEL , 20 COMPONENTS SHALL BE EMPTY .
WHEN THE TAPE WIDTH IS 44 TO 56mm , SPROCKET HOLES SHALL
BE SET ON BOTH SIDES OF REEL AS SHOWN ON THIS DRAWING .

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hirose Electric:](#)

[DF14A-9P-1.25H\(26\)](#)