






Sep.1.2021 Copyright 2021 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




POLARIZATION MARK



APRICATION DIAGRAM




RECOMMENDED PATTERN(5:1)
(RECOMMENDED BOARD THICKNESS $t=1.6\text{mm}$)



NOTES 1 :IMMERSION DEPTH INTO POTTIING SOLUTION:6.5mm

1	PBT	WHITE, UL94V-0	3	HIPS	TRAY
			2	BRASS	SURFACE:TIN PLATED $1\mu\text{m}$ min UNDER PLATING:NICKEL PLATED $0.5\mu\text{m}$ min
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	
HIROSE ELECTRIC CO., LTD.		APPROVED : KI. AKIYAMA	12.07.26	DRAWING NO.	EDC3-338387-01
		CHECKED : HK. UMEHARA	12.07.26	PART NO.	DF33C-4DP-3.3DSA(24)
		DESIGNED : HT. SATO	12.07.26	CODE NO.	CL676-1113-0-24
		DRAWN : MI. SAKIMURA	12.07.26		

Sep.1.2021 Copyright 2021 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



NOTES 2 :MINIMUM UNIT OF PURCHASE SHALL BE THE QUANTITY OF CONNECTORS IN TRAY.(135 PIECES)

HRS	DRAWING NO.	EDC3-338387-01	
	PART NO.	DF33C-4DP-3. 3DSA(24)	
	CODE NO.	CL676-1113-0-24	△2/2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hirose Electric:](#)

[DF33C-4DP-3.3DSA\(24\)](#)