



- NOTES
1. THICKNESS OF PC BOARD SHALL BE 1.6mm.
  2. FIG. RECOMMENDED PC BOARD HOLE PATTERN IS SHOWN MOUNTING SIDE. HATCHING AREA SHALL BE PATTERN PROFIBITED AREA.
  3. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

2	PBT	Black, UL94V-0	6	Steel	Nickel plating $3 \mu\text{m}$ min		
1	Phosphor bronze	Contact area: Gold plating $0.3 \mu\text{m}$ min Lead area: Tin reflow plating $1 \mu\text{m}$ min Under: Nickel plating $2 \mu\text{m}$ min	5	ZDC2	Over: Nickel plating $2 \mu\text{m}$ min Under: Copper plating $1 \mu\text{m}$ min		
			4	Phosphor bronze	Nickel plating $0.8 \mu\text{m}$ min		
			3	Steel	Over: Nickel plating $3 \mu\text{m}$ min Under: Copper plating $6 \mu\text{m}$ min		
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS		
UNITS		SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm		2 : 1					
HIROSE ELECTRIC CO., LTD.			APPROVED: TU. TANIGUCHI 20200911 CHECKED: TU. TANIGUCHI 20200911 DESIGNED: MO. SHIMOMYAMA 20200911 DRAWN: MO. SHIMOMYAMA 20200911	DRAWING NO. EDC-025451-70-00 PART NO. DN20B-20S(70) CODE NO. CL0225-0045-1-70	1/1		

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hirose Electric:](#)

[DN20B-20S\(70\)](#)