



- NOTES
- 1 THE RECOMMENDED TIGHTENING TORQUE OF REF NO. ④: 0.9 TO 1 N · m.  
THE RECOMMENDED ADHESIVE AND PRIMER OF REF NO. ④: LOCTITE 243 AND LOCK PRIMER 7649 MADE BY HENKEL JAPAN LTD.
  - 2 THE RECOMMENDED TIGHTENING TORQUE OF REF NO. ⑫: 0.9 TO 1 N · m.  
THE RECOMMENDED ADHESIVE AND PRIMER OF REF NO. ⑫: LOCTITE 243 AND LOCK PRIMER 7649 MADE BY HENKEL JAPAN LTD.
  - 3 ROTATION EXAMPLE ARE SHOWN FOR REF.NO. ①, ④, ⑨, AND ⑫.
  - 4 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFER, DEPENDING ON THE CABLE STRUCTURE.  
PLEASE CONFIRM BEFORE THE USE.

5	STAINLESS STEEL		12	POLYPHENYLENE SULFIDE	(BLACK)	UL94V-0
4	ZINC ALLOY	NICKEL PLATING	11	POLYAMIDE	(WHITE)	UL94V-0
3	ZINC ALLOY	NICKEL PLATING	10	HYDROGENATION ACRYLONITRILE BUTADIENE RUBBER	(GRAY)	
2	PHOSPHOR BRONZE	CONTACT AREA :GOLD 0.2#m min. TERMINAL AREA:GOLD 0.03#m min. UNDER PLATING:NICKEL 2#m min.	9	POLYAMIDE	(BLACK)	UL94V-0
			8	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)	
			7	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)	
1	POLYPHENYLENE SULFIDE	(BLACK) UL94V-0	6	PHOSPHOR BRONZE	NICKEL PLATING	
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS	

UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
<div>HIROSE ELECTRIC CO., LTD.</div>		APPROVED	: HY. KOBAYASHI	18. 02. 26	DRAWING NO.	EDC-117790-31-00		
		CHECKED	: HY. KOBAYASHI	18. 02. 26	PART NO.	HR08D-12WLPN-10SC(31)		
		DESIGNED	: DS. MATSUNE	18. 02. 24	CODE NO.	CL108-0277-3-31		
		DRAWN	: AI. NISHIYAMA	18. 02. 22				
						1	1	

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hirose Electric:](#)

[HR08D-12WLPN-10S\(31\)](#)