


Technical drawing of a 2x20 grid of holes. The overall width is 43.18 ± 0.05 . The pitch between holes is $P = 2.54 \pm 0.05$. The hole diameter is $\varnothing 1.2 \pm 0.1$. The distance from the left edge to the first hole is 3 ± 0.05 . The distance from the last hole to the right edge is $\varnothing 0.9 \pm 0.05$. A label "THROUGH HOLE FOR MALE CONTACT" points to the rightmost hole.

1 INDICATION OF CAV. NO. AND HRS MARK CAN BE ROTATED BY 180°

1	POLYAMIDE	UL94V-0, BLACK		2	PHOSPHOR BRONZE	TIN PLATED 2 μ m min.		
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 2 : 1	COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
								
			APPROVED : MO. ISHIDA 17. 02. 03		DRAWING NO. EDC-020137-95-00			
			CHECKED : TS. MIYAZAKI 17. 02. 03		PART NO. MDF7-18S-2. 54DSA(95)			
			DESIGNED : NY. YAMASHIRO 17. 02. 02		CODE NO. CL547-0013-7-95			
	HIROSE ELECTRIC CO., LTD.	DRAWN : SN. NUMAZAKI 17. 02. 02						1/1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hirose Electric:](#)

[MDF7-18S-2.54DSA\(95\)](#)