

DRAWING FOR REFERENCE: This is subject to change without notice  
08/11/2012

1			2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△				..	△				..		
△					△				..		
△					△				..		

  

Technical drawing showing a cross-section of a connector assembly. Dimensions include: overall height 6.7 ± 0.2 (5.3), top diameter  $\phi 4.8 \pm 0.08$ , and internal diameter  $\phi 2.24 \pm 0.02$ . Callouts 1 through 5 identify components: 1 (bottom contact), 2 (press fitting), 3 (press fitting), 4 (insulator), and 5 (attached top contact).

  

3	BERYLLIUM COPPER	GOLD PLATING			
2	PTFE		5	BRASS	NICKEL PLATING
1	BERYLLIUM COPPER	GOLD PLATING	4	BERYLLIUM COPPER	GOLD PLATING
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS

  

CODE NO. (OLD) CL		DRAWN <i>K. Maki</i> 03.2.3	DESIGNED <i>K. Maki</i> 03.2.3	CHECKED <i>J. Mitani</i> 03.2.12	APPROVED <i>F. Kobayashi</i> 03.02.13	RELEASED
----------------------	--	-----------------------------------	--------------------------------------	--	---	----------

  

TO RF  		DRAWING NO. EDC4-300392	PART NO. PO40G-LJ-219
	SCALE 5 : 1	 HIROSE ELECTRIC CO., LTD.	CODE NO. CL338-0306-8
	UNITS mm		1/1

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hirose Electric:](#)

[PO40G-LJ-219](#)