CATALOG LISTING MT-4R-A28 MICRO SWITCH MT-4R-/ SWITCH - BASIC FED. MFR. CODE 91929 THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF 3 HONEYWELL THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH. -A28 2 4 **(B)** ,040 MAX. PRETRAVEL 094 DIA 4±.015 .625 **OPERATING** .63 .57 **POSITION** .25 .002 .001 .6 70 REF. **(** :140 DIA. HOLE .172 DIA. FLEXIBLE INSULATOR 1.000 (SEE NOTE !) - 1.94 REVISIONS ACO.9799 C.M.A. AUG. 55 .19 .687 BUIT B C.O. 11613 N.H.L. 31 JULY '57 AT CLOS C CO 12369 6-32 NC x .218 PER BINDER HEAD TERMINAL SCREWS (STAKED) K.L.B. DEC. 57 -.860 REF. -.31 D CO13960 MBI 22 OCT 59 E co35255 D B W MAY 75 C038589 NOTE-RER APR 77 I-MOUNTING HOLES WILL ACCEPT PINS OR SCREWS G CO-46819 OF .139 MAX. DIA. ON 1.000 2.002 CENTERS WJM 2-FOR BEST RESULTS EITHER POLARIZE THE SWITCH 26 NOV 79 WITH COMMON TERMINAL BEING OF NEGATIVE POLARITY OR MOUNT THE SWITCH WITH BRASS SCREWS AND SPACE AT LEAST .250 FROM MAGNETIC MATERIALS. CHECK CHARACTERISTICS **ELECTRICAL DATA** SCALE FULL \_12-18 OZ. CONTACT ARRANGEMENT OPERATING FORCE -----DO NOT SCALE PRINT 55 S. P. D.T. UNLESS OTHERWISE AUG. MOTOR RELEASE FORCE ----- 5 OZ. MIN SPECIFIED NON-POLARIZED 125 250 1/4 HP + IO AMPS DIMENSIONS ARE IN INCHES RESISTIVE 4 POLARIZED OR NON — MAGNETICALLY MOUNTED VOLTS D-C MOTOR TOLERANCES ARE: DRAWN DIFFERENTIAL TRAVEL ----.004 - .007 1/2 HP+ 10 AMPS ONE PLACE TWO PLACE THREE PLACE ±.036 ±.015 ±.005 ± # NOT SUITABLE FOR USE AT LESS THAN I,5 AMPS (.00) ď (.000) ANGLES Σ UND LAS. INC. LISTED RATING (NON-POLARIZED) **(C)** 

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Honeywell: MT-4R-A28