CATALOG LISTING X111577-BZ **MICRO SWITCH** BZ-2RW822725551 SWITCH - BASIC a Honeywell Division FED.MFG.CODE 91929 -.38 ±.03 SILICONE: Ø.37 X .17 WIDE BZ-2RW82272555 1.026 ± .015 **ELASTOMER** ROLLER PLUNGER SEAL COVER SEALED-TO SWITCH CASE R 1.05 ±.03 1.266 ± .015 1.188 ±.015 **FREE** Ø OPERATING POSITION **POSITION** .665 ± .030 .79 ±.02 .250 MAX $.140^{+.002}_{-.001}$ -1.000/1\+ .47 $-\emptyset.140^{+.002}_{-.001}$ HOLE 1Ø.172 Ø.085 HOLE IN 1.94 **TERMINALS** -C096055 NORM OPEN B 0011610 .687 ±.010 NM 05 MAR 05 NOTES MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF \emptyset .139 MAX ON 1.000 ± .002 CENTERS

— SEALED CONSTRUCTION PROVIDES SPLASH RESISTANCE 2 — SEALED CONSTRUCTION FROMILES 3 — CONTACT MATERIAL: GOLD ALLOY വ ANSI Y14.5M-1982 APPLIES THIRD ANGLE PROJECTION THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH DO NOT SCALE PRINT ELECTRICAL DATA **CHARACTERISTICS** SCALE CONTACT ARRANGEMENT UNLESS OTHERWISE SPECIFIED TOLERANCES ARE SPDT RELEASE FORCE ----1 1/2 OZ MIN ONE PLACE (.0) ±.030 FORMTEK DIFFERENTIAL TRAVEL ----.003-.020 L22 TWO PLACE (.00) 1A 125 VAC ±.015 OVERTRAVEL -----.094 MIN Ŋ THREE PLACE (.000) ±.005 **ANGLES** ± 1A 250V ~ T85 25E3 WEIGHT .060 LB

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Honeywell:

BZ-2RW822725551