CATALOG LISTING **MICRO SWITCH** BZ-2RW82555110T X99421-BZ SWITCH - BASIC a Honeywell Division AQB7074 FED.MFG.CODE 91929 Ø.37 X .15 WIDE SINTERED .380 ±.030 - - - -1.026 ± .015 STAINLESS STEEL ROLLER SILICONE ELASTOMER PLUNGER SEAL-R 1.9 -2RW82555110T COVER SEALED TO-SWITCH CASE 1.406 ± .030 **FREE** 1.188 ±.030 **POSITION OPERATING** .790 ± .020 .665 ± .030 **POSITION** .21 .36 .140 +.002 -.0014 يبرهم Ø.172 Ø.140 +.002 HOLE **-**1.000/  $\mathcal{C}$ 1.94 3X 6-32 UNC X (.218) -BINDING HEAD COMBINATION TERMINAL SCREW AND LOCKWASHER (SEMS) CO93346 B 0015138 .687 ±.010 മ് -.80--.78 NOTES /1\ MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF Ø .139 MAX ON 1.000 ±.002 CENTERS 2 - SEALED CONSTRUCTION PROVIDES SPLASH RESISTANCE 26 ≥ ANSI Y14.5M-1982 APPLIES S THIRD ANGLE PROJECTION THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH. DO NOT SCALE PRINT **FULL CHARACTERISTICS** ELECTRICAL DATA SCALE CONTACT ARRANGEMENT UNLESS OTHERWISE SPECIFIED TOLERANCES ARE OPERATING FORCE -- 3 1/2 OZ MAX SPDT ONE PLACE (.0) ±.030 APR RELEASE FORCE -- - - 3/4 OZ MIN  $\Box$ 15A 125, 250 OR 480 VAC TWO PLACE (.00) ±.015 ⋖ 1/8HP 125 VAC, 1/4HP 250 VAC 2  $\circ$ THREE PLACE (.000) DIFFERENTIAL TRAVEL -- -.004-.040 1/2A 125 VDC, 1/4A 250 VDC ±.005  $\mathbf{\Sigma}$ OVERTRAVEL -- -- -- .156 MIN -L288-EN<sub>05</sub> **ANGLES** ± -L306-- L315-16A 250V ~ T85 5E4 WEIGHT .076 LB

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Honeywell:

BZ-2RW82555110T