

V3L-3003-D8

CATALOG LISTING

PAGE 1 OF 1

RELEASE NO. PR-1056

M

ISSUE 17

CHECK

29APR05

AK

CHECK

9 OCT 98

J A F

CHECK

9 OCT 98


CHECK

9 OCT 98

FORMTEK

DRAWN

T S M




NOTES

- 1 - SWITCH MATERIALS WILL WITHSTAND TEMPERATURE OF 302°F
- 2 - CAUTION: OVERTRAVEL FORCE ON LEVER MUST NOT RESULT IN AN OVERTRAVEL FORCE ON PLUNGER EXCEEDING FIVE POUNDS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS	ELECTRICAL DATA	SCALE FULL	DO NOT SCALE PRINT
OPERATING FORCE - - - 195 GRAMS MAX	CONTACT ARRANGEMENT S P D T	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
RELEASE FORCE - - - - - 15 GRAM MIN	L83	ONE PLACE (.0) ± .030	
DIFFERENTIAL TRAVEL - - - .013 MAX	15.1A 1/2HP 125 OR 250 VAC	TWO PLACE (.00) ± .015	
OVERTRAVEL - - - - - .040 MIN	1/2A 125 VDC, 1/4A 250 VDC	THREE PLACE (.000) ± .005	
RELEASE TRAVEL - - - - - .007 MIN	5A 125 VAC "L"	ANGLES ±	
	Ⓣ Ⓡ Ⓢ	WEIGHT	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Honeywell:](#)

[V3L-3003-D8](#)