		REV.	CHANGE	DATE	APPD.
		· \ L V •		DAIL	
LEAD SPACING	DIA.	SYMBOL R <sub>0</sub> I <sub>MAX</sub>	THICKNESS		
RESISTANCE AT I <sub>max</sub>		R <sub>IMAX</sub>	.1 OHMS		
DIAMETER		·	.866 MAX		
THICKNESS			.245 MAX		
LEAD DIAMETER			.04 NOM		
LEAD LENGTH			1.0 MIN		
LEAD SPACING COATING MATERIAL			.310 NOM SILICONE RESIN		
TOLERANCES DRAW	S 19JUNS	450 TELE	ENWAL ELECTRONIC fortune boulevard, Milford, Massachuse phone (508) 478 – 6000 fax (50	S, IN TTS 01757 08) 473 –	U.S.A.
FRACTIONS = $\pm 1/64$ DECIMALS .XX = .01 .XXX = .005 ANGLES = 0'30'	ved date _ 6/21/S	95	OUTLINE		
USED ON	It is submi	tted in c	the property of FENWAL ELECT onfidence, and is not to be o vritten permission.		
SHEET OF DO NOT SCAL			DRAWING NUMBER		REV.
1 1 DRAWING		- A	ICL2210008-0	1	OI

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Honeywell: ICL2210008-01