FOR STRIP AND MATRIX MOUNT ASSEMBLIES

FEATURES
- Enables subpanel mounting of devices in factory assembled metal cans which are welded together in strips or matrices. Assures accurate alignment and enables pre-wiring.
- L-shaped mounting brackets conform to various panel thicknesses, using spacers.
- Simplifies panel fabrication, since only one large cutout is required.
- Facilitates printed circuit board mounting. Operating force is transmitted to mounting hardware, rather than P.C. board.
- For custom matrices contact the MICRO SWITCH Application Center.
- Mounting dimensions page 64.

AML61 MOUNTING HARDWARE ORDER GUIDE

(For standard strip mount assemblies)

AML61 B	A	5	A

Type	Mounting Bracket Orientation	Number of Cans	Mounting Bracket Location
Square cans: **AML61 B** (Plain finish) **AML61 J** (Black finish)	**A** **E**	1 2 3 4 5 6 7 8 9* 10* 11* 12* *A, C, D & E orientation only.	**A** BRACKET FLUSH TO TOP OF CAN — 0.060 **G** — 0.020 **B** **K** — 0.045 **C** — 0.030 **L** — 0.050 **D** — 0.060 **P** — 0.065 **E** — 0.120 **T** — 0.085 **F** — 1.460 **U NO BRACKETS**
Rect. cans: **AML61 E** (Plain finish) **AML61 K** (Black finish)	**B** **C** **D** ①		

① To order one rectangular can with mounting brackets on short sides, specify AML61EB1___ or AML61KB1___.

Example: **AML61EC5A**
Five rectangular cans, plain finish (un-painted), long sides abutting; type **A** mounting brackets on long sides, located flush with switch or indicator bezel. (Type **T** bracket brings top of annunciator bezel flush with top of .160 in./4,1 mm panel.)

NON-STANDARD ASSEMBLIES

Use the order form on the following page to specify non-standard AML61 strip or matrix assemblies. You may reproduce it on your office copier, or order pads from the 800 number. Request FO-63558.

This strip has Type F brackets for P.C. board mounting.

Manuals

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Honeywell](#):
  [AML61EB1E-001](#) [AML61EB5E](#) [AML61EC1E-001](#)