CATALOG LISTING **MICRO SWITCH** ASSEMBLY-13AT272-T2 FREEPORT ILLINOIS, U.S.A. TOGGLE SWITCH MILITARY P/N A DIVISION OF HONEYWELL M8805/26-007 FED. MFG. CODE 91929 N.O. TO C. CIRCUIT MADE (SWITCH NO.1) N.C. TO C. CIRCUIT MADE (SWITCH NO.2) (MAINTAINED POSITION) N.C. TO C. CIRCUITS MADE (BOTH SWITCHES) (MAINTAINED POSITION) 3 N.O. TO C. CIRCUIT MADE (SWITCH NO.2) N.C. TO C. CIRCUIT MADE (SWITCH NO. I) (MAINTAINED POSITION) 34°±8° -.072 WIDE X .038 DEEP KEYWAY TRAVEL 1271 CORROSION RESISTANT LEVER AND BUSHING 170±40 .240 DIA--15/32 NS THREAD TO WITHIN .062 OF SHOULDER HEX NUT MS25082-C21(2)/3 -.388±.010 INTERNAL TOOTH LOCKWASHER 3 DRAWING 1.160±.030 3° REF-MS35333-136 KEYING WASHER MS 25081-C4 /3 .265±.015 9 চৈত্ৰ .56 DIA SHOULDER 05 .05 × 1.082 REF .058 K FLEXIBLE INSULATORS 1.047±.030 .19 42 REVISIONS -.110 DIA .058 Д 0027739 - 84 --.050 DIA 17 AUG 70 .12--B C05 0567 JAP DEC 8 ın -.34-1.26 C CO 52725 24 MAY 83 .16 ၜၟၯႜၟႍၜၣႜၟႍၜ D co 66089 .719 MAX .33 NOTES: DAW IB FEB 91 1 - UNIT INCLUDES CAT. LIST. 21SM284-T2 (MS-25085-2) BASIC SWITCH (2) **⊕ಕ್ಷ** ⊕ಕ್ಷ ⊶⊕ 2 - TERMINALS ARE PLATED FOR SOLDERING 205421 3 HARDWARE FURNISHED ASSEMBLED WITH SWITCH OR IN G J W 24 APR 02 PACKET PER MIL-PRF-8805 4 - REPLACEMENT MOUNTING HARDWARE PACKET 15PA311-AT -.26 -34-'n Ω (l) THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH. A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH. CHARACTERISTICS **ELECTRICAL DATA** FULL CONTACT ARRANGEMENT DO NOT SCALE PRINT 2 S P D T (2) UNLESS OTHERWISE JONE NOTED SEA LEVEL 50,000 Ft. DIMENSIONS ARE IN INCHES 28 VDC Load 115 VAC **28 VDC** TOLERANCES ARE: RASTER FO-50378 = 1A m Resistive 5 5 5 ONE PLACE TWO PLACE THREE PLACE .030 (.00) ≟.015 ±.005 ± Inductive 5 3 2.5 (.000) S ANGLES Lamp 2.4 1.5 œ 2.4 WEIGHT ,075 LB MAX ⋝

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Honeywell: 13AT272-T2