



HDMI Standard Digital Interface Connector

# **DC1 Series**

CONNECTOR MB-0121-3 February 2013



The market for digital consumer devices such as LCD TVs, BD players has been rapidly growing along with the progress of digital high-definition television broadcasting.

The DC1 Series is a connector created specifically for use with the HDMI standard, a digital interface standard for digital consumer devices.

\*HDMI, the HDMI Logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

#### Features

■1.0mm pitch, compact connector.

■Impedance-matching design for high-speed transmission.

■Grounding structure for excellent EMI control.

Friction lock for easy insertion and removal of connector.

#### **Applicable Markets**

LCD television, LCD projector, Set-top box, BD player, etc.

General Specifications

■No. of Contacts: 19 pos.

Dielectric Withstanding Voltage :

AC 500V rms

■Rated Voltage: 0.5A max.

Insulation Resistance: 100M  $\Omega$  min.

■Impedance: 100 Ω ±15%

■Operating Temperature:

-20 Deg. C to +85 Deg. C

Materials and Finishes

#### Receptacle


Component	Material / Finish			
Insulator	Heat resistant plastic			
Contact	Copper alloy / Au plating over Ni			
Shell	Copper alloy / Sn plating			

## Plug (for Cable Harness)


Component	Material / Finish			
Insulator	Heat resistant plastic			
Contact	Copper alloy / Au plating over Ni			
Shell	Copper alloy / Sn plating			
Hood	PVC / Color: Black (UL94V-0)			

### Ordering Information

•Receptacle




### •HDMI-HDMI Cable Harness




Dimensions and Shape

Right Angle Receptacle

•DC1RS19JA7 (SMT, without flange)







## Right Angle Receptacle

## •DC1RS19JAX


(SMT, with right angle flange)






## Straight Receptacle


## •DC1RS19WA7






Applicable Board Dimensions (for reference)

• DC1RS19JA7, JAX




DC1RS19WA7



## HDMI-HDMI Cable Harness

## •DC1P019ST3\*\*\*\*B



Drawing Number

## Receptacle

Connection	Mounting	Flange	Part Number	SJ Drawing	Specification
<b>Right Angle</b>	SMT	No	DC1RS19JA7	SJ112283	JACS-3289
		Yes	DC1RS19JAX	SJ112619	
Straight	SMT	Yes	DC1RS19WA7	SJ112330	

## Cable Harness

Cable Harness	Harness	Part Number	SJ Drawing	Specification
	HDMI-HDMI	DC1P019ST3****B	SJ038524	JACS-3289
		DC1P019ST8****B	SJ100180	

### •DC1 Series Connector, Cable Handling Instruction------JAHL-3289

for the applications listed below. However, if the above-mentioned products are to be used in aerospace devices, marine cable-connection devices, atomic power control systems, medical equipment for lifesupport systems, or any other specific application requiring extremely high reliability, please contact JAE for further information. Recommended applications: Computers, Office machines, Measuring devices, Telecommunication devices (Terminals, Mobile devices), AV devices, Household applications, FA devices, etc.

**Notice:** Products shown in this brochure are made

#### Japan Aviation Electronics Industry, Limited

Product Marketing Division Aobadai Building, 3-1-19, Aobadai, Meguro-ku, Tokyo 153-8539 Phone: +81-3-3780-2882 FAX: +81-3-3780-2946

\* The specifications in this brochure are subject to change without notice. Please contact JAE for information.

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JAE Electronics:

DC1P019ST30300B DC1P019ST30300Z DC1P019ST30150B DC1RS19JAXR190 DC1RS19WA7