

	製図 DR、	担当 CHK.		查閲 APPD.	承認 APPD.	
		L				
				\sim		
٦				N		
7				<u> </u>		
(0 N T A O T S	1.1)		\backslash	PCB		
5.8)						
-1						
<u>CONDITION(REF.)</u> 嵌合状態図(参考)						
嵌合状態凶(参考)						
RMINAL AND HOLD DOWN Bmm MAX.						
ARE APPROPRIATE FOR GROUND CONTACTS.						
AND PRODUCT NAME AS INDICATED.						
ンの相互のバラツキは0.08以内である。						
ンタクトと						
名を表示す	3.	<u></u>				
TIN PLAT	ING				······	
-				UL94 V-0 BI	EIGE	
TIN PLAT	ING				<u> </u>	
CONTACT AREA : TERMINAL AREA : GOLD OVER NICKEL TIN OVER NICKEL						
(SCALE)		ERIES)	7	TUR.		
5:1 FI-X 日本航空電子工業株式会社						٩٩
称(TITLE) UAPAN AVIATION						
FI-XB30SSLA					RONICS	Z E
-HF15 INDUSTRY, LTD.						I S
(PCB	SIDE)	F		面番号(DRAWI	NG NO.)	版数 (REV.)
(MASS)				SJ110	100	1
	IV. PROPRIET					L
			21 6	CTRONICO IN		

COPYRIGHT (C) 2009, JAPAN AVIATION ELECTRONICS INDUSTRY, LTD.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JAE Electronics: FI-XB30SSLA-HF15