

NOTES:

- 1. FLASHER TYPE LAMPS HAVE A BI-METAL STRIP ADDED TOTHE FILAMENT MOUNT TO PROVIDE THE FLASHING. HEAT FROM THE FILAMENT CAUSES THIS STRIP TO BEND AWAY FROM THE LEAD WIRE, BREAKING THE CIRCUIT. AS THE BI-METAL STRIP COOLS IT RETURNS TO IT'S ORIGINAL POSITION AGAINST THE LEAD WIRE AND THE LAMP LIGHTS.
- 2. FLASHER TYPE LAMPS ARE DESIGNED TO RANDOMLYBLINK AT THE APPROX-IMATE RATE OF 50-150 FLASHERS PER MINUTE A NORMAL ROOM TEMPERATURE, SOME WILL BE OUTSIDE THIS RANGE. AS AMBIENT TEMPERATURE AND/OR INPUT VOLTAGE CHANGES, THE FLASH RATE MAY VARY CONSIDERABLY.

		Α		REV.	
		ADD NOTES	RELEASED	DESCRIPTION/ECO NO.	
		6/15/01	3/2/01	DATE	

RB22	1835	1828	1822	1873	313	1864	1820	757	1829	1819	1818	1892	1813	1893	*256	1891	1815	756	1816	1888	44	1866	47	755	316	1850	45	1490	43	1436	49	NUMBER	JKL LAMP
130.0	55.0	37.5	36.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	24.0	14.4	14.4	14.0	14.0	14.0	14.0	14.0	13.0	7.0	6.3	6.3	6.3	6.3	6.0	5.0	3.2	3.2	2.5	2.5	2.0	RATED	VOLTS
.027	.050	.050	.100	.200	.170	.170	.100	.080	070.	.040	.170	.120	.100	.330	.270	.240	.200	.080	.330	.500	.250	.250	.150	.150	.700	.090	.350	.160	.500	.300	090.	±10%	SHWY
.600	1.10	.65	2.10	3.00	3.50	3.00	1.60	.62	1.00	.34	3.30	.75	.86	2.00	1.60	2.00	1.40	.31	3.00	2.00	.90	.65	.52	.33	3.40	.25	.50	.20	.50	.30	.04	±25%	MSCP
7.54	13.83	8.17	26.40	37.71	44.00	37.71	20.11	7.79	12.57	4.27	41.48	9.43	10.81	25.14	20.11	25.14	17.60	3.90	37.71	25.14	11.31	8.17	6.54	4.15	42.74	3.14	6.29	2.51	6.29	3.77	0.50	±25%	SNBMOT
5,000	5,000	3,000	1,000	7,000	500	1,500	1,000	15,000	1,000	2,500	250	1,000	1,000	7,500	500	500	3,000	15,000	1,000	3,000	3,000	10,000	3,000	20,000	500	1,500	3,000	3,000	3,000	1,000	1,000	LIFE HRS.	AVERAGE
C-5	C-2F	C-2F	C-2F	C-2F	C-2F	C-2V	C-2F	C-2R	C-2F	C-2V	C-2F	C-2V	C-2R	C-2R	C-2R	C-2R	C-2V	C-2R	C-2R	C-2R	C-2R	C-2R	C-2R	S-2	TYPE	FILAMENT							

*FLASHER TYPE LAMP

			•
- CAD D MANUAL REVISION	DRAWN BY APPV'D BY DAT L. WENGSTROM QC 6/15/01	THIRD ANGLE PROJECTION	METRIC +-+
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED	П	1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0	DIMENSIONS ARE IN MILLIMETERS
SCALE	SIZE A	דודרוב דודרוב	J
NONE	55335 NO. B	-3 1/4 M	KI
RELEASED REVISION DATE	55335 NO. BAYONET SINGLE CONTACT T-3 1/4	: T-3 1/4 MINIATURE SINGLE CONTACT BAYONET	JKL COMPONENTS CORPORATION
REVISION DATE	SINC	IGLE	ENTS
N 6/15/01 $^{REV.}$ A I I SHEET	SLE CON	CONTAC	CORP
NO. A	гаст т	т ваүс	ORAT
SHEET 1 OF 1	[-3 1/ ₂	DNET	NOI

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JKL Components:

<u>1490</u> <u>1815</u> <u>1819</u> <u>1820</u> <u>1822</u> <u>1829</u> <u>1835</u> <u>1864</u> <u>1891</u> <u>1893</u> <u>313</u> <u>316</u> <u>47</u> <u>755</u> <u>756</u> <u>1436</u> <u>1813</u> <u>1818</u> <u>1828</u> <u>43</u> <u>1850</u> <u>1816</u> <u>1873</u> <u>45</u>