

JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE	
11	2.5	.200	.200	2.51	500	C-2R	
56	5.0	.115	.150	1.89	40,000	C-2R	
79	6.0	.200	.630	7.92	1,000	C-2R	
86	6.3	.200	.400	5.03	50,000	C-2F	
18	14.0	.040	.130	1.63	5,000	C-2F	
73*	14.0	.080	.300	3.77	15,000	C-2F	
37	14.0	.090	.500	6.29	2,500	C-2F	
74	14.0	.100	.700	8.80	500	C-2F	
85	28.0	.040	.300	3.77	25,000	C-2F	
17	28.0	.065	.650	8.17	5,000	C-2F	

*LAMP LEAD (Pb) FREE

CONTACT JKL FOR LEAD (Pb) FREE LOT IDENTIFICATION.

			METRIC	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS		JKL COMPONENTS CORPORATION					ION	
			THIRD ANGLE PROJECTION		OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0			3/4 STANDARD GLASS WEDGE I		SE BASE	3ASE	
			DRAWN BY	APPV'D B	Y DATE	SIZE	FSCM NO.					
Α	NOTE #73 TO LEAD (Pb) FREE		L. WENGSTROM	J.K.	2/17/05	Α	55335	NO. GLAS	SS WEDGE B	ASE T-	1 3/4	
	RELEASED & CANCEL GW-STD-T1 3/4, 75X & 84	5/11/00	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE	•	RELEASED	REVISION	REV.	SHEET	
RE\ NO.	/. DESCRIPTION/ECO NUMBER	APPV'D DATE					NONE	DATE 5/11/00	DATE 2/17/05	NO. A	1 _{OF} 1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JKL Components:

18