

Power Supplies Data Sheet

Single Output Power Supplies

Power With Confidence

Current: Up to 30 Amps Voltage: Up to 60 Volts Power: Up to 360 Watts

Switching D.C. Power Supply

The T3PS1000 Series is single output, 360 W, switching DC power supply. OVP protects the T3PS1000 Series and their load from unexpected conditions. High regulation is maintained at 0.01%. Remote sensing adds an extra level of precision by compensating for cable losses between the power supply and load. Turning the output On/Off from an external device is available through Remote control terminals. The T3PS1000 Series is an ideal solution for power-efficient bench-top or portable applications requiring high regulation.



Tools for Improved Debugging

- Dual Measurement Display.
- Switched Mode high efficiency Power Supply Design.
- Constant Voltage and Constant Current Operation.
- Rear mounted remote sense terminals.
- Remote Output On / Off Control (not programmable)
- Only 128 mm Wide x 151 mm High x 295 mm Deep. Weight Approx. 3.2 kg.

- Clearly see your power settings.
- Small footprint whilst maintaining high power density.
- Wider application coverage for a more complete solution.
- Ensure that the full voltage gets to your DUT. Sense compensates for wiring losses.
- Turn the output On or Off from an external device.
- High power / high performance whilst take up the minimum of bench space.

Models and Characteristics

T3PS11230	0 – 12 V	0 – 30 A	360 W
T3PS12415	0 – 24 V	0 – 15 A	360 W
T3PS16006	0 - 60 V	0 – 6 A	360 W

FEATURES AND SPECIFICATIONS



T3PS1000 Series

- Dual Measurement Display
- 0.01% High Regulation
- Constant Voltage and Constant Current Operation
- High Efficiency
- High Power Density
- Over Voltage Protection
- Remote Output ON/OFF Control

Rear Panel

Model T3PS11230 T3PS12415 T3PS16006 Output 0~12V 0~24V 0~60 V Voltage 0~30 A 0~15A $0 \sim 6 A$ Current **Constant Voltage Operation** Regulation Line regulation ≤ 5 mV, Load regulation ≤ 5 mV ≤ 5 mVrms, 100 mVp-p 20 Hz ~ 20 MHz Ripple & Noise ≤ 500 S (50 % Load change, Minimum load 0.5 A) RecoveryTime Temp. Coefficient ≤ 100 ppm / °C 0 to rating voltage continuously adjustable Output Range **Constant Current Operation** Regulation Line regulation \leq 3 mA, Load regulation \leq 3 mA **Ripple Current** ≤ 3 mArms (T3PS16006) ≤ 10 mArms (T3PS12415) ≤ 30 mArms (T3PS11230) Output Range 0 to rated current continuously adjustable (HI/LO range switchable) Meter 3 1/2 digit, 0.39" LED display Туре Accuracy \pm (0.5% of rdg + 2 digits) Insulation Chassis and Terminal 20 M Ω or above (DC 500V) Chassis and AC Cord 30 MΩ or above (DC 500V) **Power Source** AC 115 V/ 230 V ± 15%, 50/60 Hz **Dimensions & Weight** 128 (W) x 151 (H) x 295 (D) mm, Approx. 3.2 kg

Ordering information

Models	T3PS11230	360 W Switching D.C. Power Supply	
	T3PS12415	360 W Switching D.C. Power Supply	
	T3PS16006	360 W Switching D.C. Power Supply	
Accessories	Quick Start Guide x 1, Power cord x 3, Test lead GTL-203 A x 1		

Warranty: 3 Years return to Teledyne LeCroy.

ABOUT TELEDYNE TEST TOOLS



Company Profile

Teledyne LeCroy is a leading provider of oscilloscopes, protocol analyzers and related test and measurement solutions that enable companies across a wide range of industries to design and test electronic devices of all types. Since our founding in 1964, we have focused on creating products that improve productivity by helping engineers resolve design issues faster and more effectively. Oscilloscopes are tools used by designers and engineers to measure and analyze complex electronic signals in order to develop high-performance systems and to validate electronic designs in order to improve time to market.

The Teledyne Test Tools brand extends the Teledyne LeCroy product portfolio with a comprehensive range of test equipment solutions. This new range of products delivers a broad range of quality test solutions that enable engineers to rapidly validate product and design and reduce time-tomarket. Designers, engineers and educators rely on Teledyne Test Tools solutions to meet their most challenging needs for testing, education and electronics validation.

Location and Facilities

Headquartered in Chestnut Ridge, New York, Teledyne Test Tools and Teledyne LeCroy has sales, service and development subsidiaries in the US and throughout Europe and Asia. Teledyne Test Tools and Teledyne LeCroy products are employed across a wide variety of industries, including semiconductor, computer, consumer electronics, education, military/aerospace, automotive/industrial, and telecommunications.

Distributed by:

Teledyne LeCroy (US Headquarters)

700 Chestnut Ridge Road Chestnut Ridge, NY. USA 10977-6499

Phone:	800-553-2769 or 845-425-2000
Fax Sales:	845-578-5985
Phone Support:	1-800-553-2769
Email Sales:	contact.corp@teledynelecroy.com
Email Support:	support@teledynelecroy.com
Web Site:	http://teledynelecroy.com/

World wide support contacts can be found at: https://teledynelecroy.com/support/contact

World wide instrument service can be found at: https://teledynelecroy.com/support/service.aspx

RoHS and WEEE information can be found at: https://teledynelecroy.com/support/rohs.aspx

Teledyne LeCroy (European Headquarters)

Teledyne LeCroy GmbH Im Breitspiel 11c D-69126 Heidelberg, Germany

Phone:	+49 6221 82700
Fax:	+49 6221 834655
Phone Service:	+49 6221 8270 85
Phone Support:	+49 6221 8270 28
Email Sales:	contact.gmbh@teledynelecroy.com
Email Service:	service.gmbh@teledynelecroy.com
Email Support:	tlc.t3.appsupport.eu@teledyne.com
Web Site:	http://teledynelecroy.com/

teledynelecroy.com

© 2019 Teledyne Test Tools is a brand and trademark of Teledyne LeCroy Inc. All rights reserved. Specifications, prices, availability and delivery subject to change without notice. Product brand or brand names are trademarks or requested trademarks of their respective holders. T3 stands for Teledyne Test Tools.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

 Teledyne LeCroy:

 T3PS11230
 T3PS16006
 T3PS12415