

## **MIRA-WW**

~60° wide beam

### **SPECIFICATION:**

Dimensions Ø 32.4
Height 14.7 mm
Fastening glue
ROHS compliant yes ①



### **MATERIALS:**

ComponentTypeMaterialColourFinishLength (mm)MIRA-WWSingle lensPCclear


#### **ORDERING INFORMATION:**

» Box size: 480 x 280 x 300 mm

Component Qty in box MOQ MPQ Box weight (kg)

C12502\_MIRA-WW 840 120 60 7.3






See also our general installation guide: <a href="www.ledil.com/installation\_guide">www.ledil.com/installation\_guide</a>





LED BXRA ES Star
FWHM / FWTM 54.0° / 88.0°
Efficiency 83 %
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

bridgelux.

LED V10 Gen6
FWHM / FWTM 56.0° / 92.0°
Efficiency 78 %
Peak intensity 0.9 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:





Light distribution files


CREE -

LED CXA/B 15xx
FWHM / FWTM 53.0° / 87.0°
Efficiency 84 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:














LED LUXEON M/MX FWHM / FWTM 57.0° / 90.0°
Efficiency 82 %
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

## **UMILEDS**


LED LUXEON MZ
FWHM / FWTM 49.0° / 82.0°
Efficiency 81 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

## **WNICHIA**

LED NFMW48xA
FWHM / FWTM 50.0° / 83.0°
Efficiency 82 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



## **WNICHIA**

 LED
 NSCxL036A

 FWHM / FWTM
 57.0° / 89.0°


 Efficiency
 79 %

 Peak intensity
 0.9 cd/lm

 LEDs/each optic
 1

 Light colour/type
 White


 Required components:



Light distribution files

## **WNICHIA**

LED NSMx286M
FWHM / FWTM 47.0° / 80.0°
Efficiency 76 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

#### OSRAM Opto Semiconductors

LED Duris \$10
FWHM / FWTM 54.0° / 84.0°
Efficiency 86 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files



## **OPTICAL RESULTS (SIMULATED):**



LED VERO10
FWHM / FWTM 51.2° / 84.8°
Efficiency 88 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED LUXEON 5258
FWHM / FWTM 54.0° / 76.0°
Efficiency 92 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour/type White

Required components:

Light distribution files




LED LUXEON 7070
FWHM / FWTM 69.0° / 94.0°
Efficiency 88 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



## **OPTICAL RESULTS (SIMULATED):**





# PRODUCT DATASHEET C12502 MIRA-WW

#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDIL Oy

Joensuunkatu 7 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Poznan, Poland Hong Kong, China

#### **Distribution Partners**

www.ledil.com/ where\_to\_buy

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Ledil:

C12502\_MIRA-WW