

## LINNEA-GC2-WG

Narrow asymmetric oval beam for wall grazing

## SPECIFICATION:

Dimensions	43.0 x 283.6 mm
Height	15.2 mm
Fastening	clips
ROHS compliant	yes ⓘ


## MATERIALS:

Component	Type	Material	Colour	Finish	Length
LINNEA-GC2-WG	Linear lens	PMMA	clear		43.0

## ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
F17724_LINNEA-GC2-WG » Box size: 398 x 298 x 265 mm	120	32	8	10.2






See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

### OPTICAL RESULTS (MEASURED):

#### CITIZEN

LED CLUC11  
FWHM / FWTM Asymmetric  
Efficiency 80 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED Bridgelux SMD 2835  
 FWHM / FWTM Asymmetric  
 Efficiency 89 %  
 Peak intensity 1.9 cd/Im  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED J Series 2835  
 FWHM / FWTM Asymmetric  
 Efficiency 91 %  
 Peak intensity 1.9 cd/Im  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED J Series 3030  
 FWHM / FWTM Asymmetric  
 Efficiency 91 %  
 Peak intensity 1.8 cd/Im  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED LUXEON 3030 HE Plus  
 FWHM / FWTM Asymmetric  
 Efficiency 91 %  
 Peak intensity 1.9 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED LUXEON 3535L HE PLUS  
 FWHM / FWTM Asymmetric  
 Efficiency 91 %  
 Peak intensity 1.8 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED NF2W585AR-P8  
 FWHM / FWTM Asymmetric  
 Efficiency 92 %  
 Peak intensity 1.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED NF2W757G-MT (Tunable White)  
 FWHM / FWTM Asymmetric  
 Efficiency 91 %  
 Peak intensity 1.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type Tunable White  
 Required components:



Light distribution files




LED NFSW757H  
 FWHM / FWTM Asymmetric  
 Efficiency 91 %  
 Peak intensity 1.8 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED NFSx757G  
 FWHM / FWTM Asymmetric  
 Efficiency 91 %  
 Peak intensity 1.8 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):

**OSRAM**  
Opto Semiconductors


LED Duris E 2835  
FWHM / FWTM Asymmetric  
Efficiency 91 %  
Peak intensity 1.9 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors


LED Duris S5 (2 chip)  
FWHM / FWTM Asymmetric  
Efficiency 91 %  
Peak intensity 1.9 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

**OSRAM**  
Opto Semiconductors

LED OSCONIQ C 2424  
FWHM / FWTM Asymmetric  
Efficiency 92 %  
Peak intensity 2 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

## OPTICAL RESULTS (SIMULATED):

### SAMSUNG

LED	LM28xB Series
FWHM / FWTM	Asymmetric
Efficiency	90 %
Peak intensity	1.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Ledil:](#)

[C17724\\_LINNEA-GC2-WG](#)