# PRODUCT DATASHEET CP18574\_AMY-110-WW-C

#### AMY-110-WW-C

 ${\sim}60^{\circ}$  wide beam. Assembly with holder C compatible with LEDiL HEKLA. Black version.

#### **TECHNICAL SPECIFICATIONS:**

Dimensions Ø 109.7 mm

Height 23.4 mm

ROHS compliant yes ①



#### **MATERIAL SPECIFICATIONS:**

ComponentTypeMaterialColourFinishAMY-110-WWSingle lensPMMAclearAMY-110-HLD-CHolderPCblack

#### **ORDERING INFORMATION:**


» Box size: 480 x 280 x 300 mm

Component Qty in box MOQ MPQ Box weight (kg)

CP18574\_AMY-110-WW-C 77 77 9.3



## **PRODUCT** CP18574\_AMY-110-WW-C



See also our general installation guide: <a href="www.ledil.com/installation\_guide">www.ledil.com/installation\_guide</a>

2/4

# PRODUCT DATASHEET CP18574\_AMY-110-WW-C

#### PHOTOMETRIC DATA (SIMULATED):

bridgelux


LED V18 Gen 8 FWHM / FWTM 60.0° / 84.0°

Efficiency 82 %
Peak intensity 0.9 cd/lm

LEDs/each optic 1
Light colour White

Required components:

C16142\_HEKLA-SOCKET-K Bender Wirth: 462 Typ L8



bridgelux


LED Vesta TW 18mm (31W) DP

FWHM / FWTM 59.0° / 82.0°
Efficiency 82 %
Peak intensity 0.9 cd/lm
LEDs/each optic 1

Light colour Tunable White

Required components:

C16142\_HEKLA-SOCKET-K Bender Wirth: 462 Typ L8



**CITIZEN** 


LED CLL03x/CLU03x

FWHM / FWTM 56.0° / 80.0° Efficiency 87 %

Peak intensity 1.1 cd/lm LEDs/each optic 1

Light colour White

Required components: F17438\_HEKLA-G2-I



**SAMSUNG** 

LED LC016D / LC019D / LC026D / LC033D

FWHM / FWTM 58.0° / 80.0°


Efficiency 87 %

Peak intensity 1.1 cd/lm

LEDs/each optic 1

Light colour White

Required components: F17438\_HEKLA-G2-I



3/4



### PRODUCT DATASHEET CP18574\_AMY-110-WW-C

#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

## Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

## Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

www.ledil.com/ where\_to\_buy

### **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Ledil:

CP18574\_AMY-110-WW-C