

ADELY-50-S

~15° spot beam

SPECIFICATION:

Dimensions Ø 49.6
Height 28.1 mm
Fastening clips, socket
ROHS compliant yes ①



MATERIALS:

Component	Туре	Material	Colour	Finish	Length (mm)
ADELY-50-S	Reflector	Aluminium	metal		
YASMEEN-50-HLD2-B	Holder B	PC	black		
YASMEEN-50-HLD2-C	Holder C	PC	black		

ORDERING INFORMATION:

Quantities for one set:


Reflector 1 Holder 1



PRODUCT DATASHEET ADELY-50-S

Component		Qty in box	MOQ	MPQ	Box weight (kg)
C18891_ADELY-50-S » Box size: 370 x 300 x 310 mm	Reflector	1600	80	80	12.6
C18694_YASMEEN-50-HLD2-B » Box size: 400 x 300 x 300 mm	Holder	750	60	10	5.5
C18691_YASMEEN-50-HLD2-C » Box size: 400 x 300 x 300 mm	Holder	500	60	10	3.7






See also our general installation guide: www.ledil.com/installation_guide

Published: 17/08/2023



OPTICAL RESULTS (MEASURED):



Published: 17/08/2023



OPTICAL RESULTS (SIMULATED):




LED BXRV-D13-RGBW3000-A3

FWHM / FWTM 24.0° / 60.0°
Efficiency 73 %
Peak intensity 2.5 cd/lm
LEDs/each optic 48
Light colour/type RGBW

Required components:

C19950_HEKLA-SOCKET-RZ





Light distribution files

CITIZEN

LED CLU700/701/702/703


 FWHM / FWTM
 12.0° / 22.0°

 Efficiency
 89 %

 Peak intensity
 11.4 cd/lm

LEDs/each optic 1
Light colour/type White

Required components: F17435_HEKLA-G2-C



Light distribution files





GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 7 FI-24100 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Poznan, Poland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Ledil:

C18691_YASMEEN-50-HLD2-C C18694_YASMEEN-50-HLD2-B C18891_ADELY-50-S