

HEIDI

Ø21.6 mm easily sealable TIR-lenses for up to 3535 size LED packages

TIR-lens with multiple beam patterns designed to be easily protected against the environment by conformal coatings. Available with or without two-sided adhesive tape.




PRODUCTS:

C13738_HEIDI-M-NP


CA14000_HEIDI-M-NP

CA12242_HEIDI-SS



Dimensions: 21.6 mm x 21.6 mm
Height: 11.60 mm
 ~25° medium beam. Version without location pins.


Dimensions: 21.6 mm x 21.6 mm
Height: 11.60 mm
 ~25° medium beam. Version without location pins.



Dimensions: 21.6 mm x 21.6 mm
Height: 11.70 mm
 ~15° smooth spot beam


PRODUCTS:

CA12538_HEIDI-W




Dimensions: 21.6 mm x 21.6 mm
Height: 11.70 mm
 ~30° wide beam optimized for
 LUXEON Rebel ES

CA11267_HEIDI-O-90




Dimensions: 21.6 mm x 21.6 mm
Height: 12.10 mm
 ~13° x 45° oval beam optimized for
 Cree XP-G and XP-E. Variant with
 beam direction rotated 90°.

CA14197_HEIDI-REC-90




Dimensions: 21.6 mm x 21.6 mm
Height: 12.85 mm
 ~35° + 55° rectangular beam

CA12443_HEIDI-SS




Dimensions: 21.6 mm x 21.6 mm
Height: 11.70 mm
 ~15° smooth spot beam optimized
 for LUXEON Rebel ES

CA12815_HEIDI-O-90



Dimensions: 21.6 mm x 21.6 mm
Height: 11.70 mm
 ~13° x 45° oval beam optimized for
 Luxeon Rebel. Variant with beam
 direction rotated 90°.


CA11268_HEIDI-W



Dimensions: 21.6 mm x 21.6 mm
Height: 11.70 mm
 ~32° wide beam


PRODUCTS:

CA12530_HEIDI-D




Dimensions: 21.6 mm x 21.6 mm
Height: 11.70 mm
 ~10° diffused spot beam optimized
 for LUXEON Rebel ES

CA11264_HEIDI-D




Dimensions: 21.6 mm x 21.6 mm
Height: 11.90 mm
 ~10° diffused spot beam

CA12949_HEIDI-O




Dimensions: 21.6 mm x 21.6 mm
Height: 11.70 mm
 ~50° x 11° oval beam

CA11663_HEIDI-RS




Dimensions: 21.6 mm x 21.6 mm
Height: 11.70 mm
 ~8° spot beam

CA12536_HEIDI-M



Dimensions: 21.6 mm x 21.6 mm
Height: 11.70 mm
 ~25° medium beam


CA11265_HEIDI-M



Dimensions: 21.6 mm x 21.6 mm
Height: 11.90 mm
 ~25° medium beam

PRODUCTS:

CA12079_HEIDI-W2




Dimensions: 21.6 mm x 21.6 mm

Height: 12.00 mm

~45° wide beam

CA12537_HEIDI-RS




Dimensions: 21.6 mm x 21.6 mm

Height: 11.70 mm

~8° spot beam

CA11266_HEIDI-O



Dimensions: 21.6 mm x 21.6 mm

Height: 11.90 mm

~50° x 11° oval beam

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Ledil:](#)

[C12085_HEIDI-W2](#)