

HEN.1F.308.CLNP

SUMMARY

Wires

Series

IP rating

Cable Ø

Status

Low voltage

Termination type

AWG wire size

Matching parts

Female print PCB

30.00 - 22.00

0.00 - 0.00 mm

FGN.1F.308.CLC

8

1F

68

active

	-	6
	1	

Image is for illustrative purpose only

Download					
	Request a quote				
	PCB Fadle Patter				

PCB Eagle Pattern PCB Altium Pattern PCB KiCad Pattern Catalog

TECHNICAL DETAILS

Mechanics

Ρ

Shell Style/Model	HE*: Fixed receptacle, nut fixing, for printed circuit (back panel mounting)
Keying	3 keys (beta=165, gamma=30, plug: male contacts, receptacle: female contacts)
Housing Material	Brass (chrome plated [SAE AMS 2460]) shell and nut, other pieces brass
Variant	P:Watertight
Weight	11.78 g
Performance	

Configuration	1F.308 : 8 Low Voltage
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated Current	5 Amps

Specifications


Contact Type: Print (straight) Contact Dia.: 0.7 mm (0.028in) R (max): 6.1 mOhm Vtest (contact-shell): 1300 V (AC), 1840 V (DC) Vtest (contact-contact): 1300 V (AC), 1840 V (DC)


Others


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Endurance (Shell): 5000 mating cycles Temp (min / max): -50°C / +150°C Humidity (max): <=95% [at 60 deg C /140 F] Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Climatical Category: 50/175/21 (Aluminium shell) Salt Spray Corrosion: >1000 hr Pressure: 5 bars

DRAWINGS







Dimensions

	А	В	E	Н	L	Μ	Р	S1	S2	Х	e
mm.	17	17	3	7.62	21.5	3.2	14.5	11.5	14	17.5	M13x0.75
in.	0,67	0,67	0,12	0,30	0,85	0,13	0,57	0,45	0,55	0,69	

RECOMMENDED BY LEMO

Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

LEMO: HEN.1F.308.CLNP