Datasheet



ADP-SMAM-SMBF-G SMA Plug to SMB Jack Adapter

The ADP-SMAM-SMBF-G is an SMA plug to SMB jack adapter. Operating from 0 GHz to 4 GHz, the ADP-SMAM-SMBF-G combines superior performance, compact size, and a convenient snap-on mating interface to provide a reliable, easy-to-use adapter. Additionally, all Linx adapters meet RoHS lead free standards and are tested to meet requirements for corrosion resistance, vibration, mechanical and thermal shock.



- 0 to 4 GHz operation
- Gold plating
 - Superior corrosion resistance
- SMA plug (male pin) connection
 - Gold plated brass center contact
- SMB jack (male pin) connection
 - Gold plated brass center contact

Applications

- LPWA
 - LoRaWAN[®], Sigfox[®], WiFi HaLow[™] (802.11ah)
- Cellular IoT
 - LTE-M (Cat-M1), NB-IoT
- Cellular
 - 5G/4G LTE/3G/2G
- GNSS
 - GPS, Galileo, GLONASS, BeiDou, QZSS
- Industrial/Commercial/Enterprise
- ISM

Table 1. Electrical Specifications

Impedance	50 Ω	
Frequency Range	0 to 4 GHz	
Voltage Rating	750 V RMS	
Contact Resistance	Center: $\leq 6.0 \text{ m}\Omega$ Outer: $\leq 2.0 \text{ m}\Omega$	
Select Frequencies	400 MHz to 960 MHz	2.4 GHz
Insertion Loss (dB max)	-0.08	-0.14
VSWR (max)	1.0	1.0

Ordering Information

Part Number	Description	
ADP-SMAM-SMBF-G	SMA plug (male pin) to SMB jack (male pin) adapter	

Available from Linx Technologies and select distributors and representatives.

Product Dimensions




Figure 1. Product Dimensions for the ADP-SMAM-SMBF-G Adapter

Table 2.	Adapter	Components
----------	---------	------------

ADP-SMAM-SMBF-G	Connector A SMA plug (male pin)		Connector B SMB jack (male pin)	
Connector Part	Material	Finish	Material	Finish
Body	Brass	Gold	Brass	Gold
Center Contact	Brass	Gold	Brass	Gold
Insulator	PTFE	-	PTFE	-

Adapter Performance

Table 3 shows insertion loss and VSWR values for the ADP-SMAM-SMBF-G adapter at commonly used frequencies.

Insertion loss is the loss of signal power (gain) resulting from the insertion of a device in a transmission line. VSWR describes how efficiently power is transmitted through the adapter. A lower VSWR value indicates better performance at a given frequency.

Band	Low-Band Cellular/ ISM/LPWA	GNSS	Midband Cellular	WiFi/ISM
Frequency Range	400 MHz to 960 MHz	1164 MHz to 1609 MHz	1427 MHz to 5000 MHz	2.4 GHz
Insertion Loss (dB max)	-0.08	-0.12	-0.21	-0.14
VSWR (max)	1.0	1.0	1.2	1.0

Table 3. Insertion Loss and VSWR for the ADP-SMAM-SMBF-G Adapter



Datasheet

Table 4. Mechanical Specifications			
ADP-SMAM-SMBF-G	Connector AConnector BSMA plug (male pin)SMB jack (male pin)		
Mounting Type	Inline, Free-hanging		
Fastening Type	1/4"-36UNS Threaded Coupling Snap-on Coupling		
Interface in Accordance with	MIL-STD-348A	MIL-STD-348A	
Recommended Torque	0.57 N·m (5.0 in·lbs)	n/a	
Coupling Nut Retention	60 lbs min.	n/a	
Durability	500 cycles min. 500 cycles min.		
Weight	4.7 g (0.16 oz)		

Table 4. Mechanical Specifications

Table 5. Environmental Specifications

MIL-STD, Method, Test Condition		
Corrosion (Salt spray)	MIL-STD-202 Method 101 test condition B	
Thermal Shock	MIL-STD-202 Method 107 test condition B	
Vibration	MIL-STD-202 Method 204 test condition B	
Mechanical Shock	MIL-STD-202 Method 213 test condition I	
Temperature Range	-65 °C to +165 ° C	
Environmental Compliance	RoHS	

Packaging Information

The ADP-SMAM-SMBF-G adapter is sealed in a plastic bag of 50 pcs. Bags are placed in cartons (4000 pcs.) Distribution channels may offer alternative packaging options.



Website:http://linxtechnologies.comLinx Offices:159 Ort Lane, Merlin, OR, US 97532Phone:+1 (541) 471-6256E-MAIL:info@linxtechnologies.com

Linx Technologies reserves the right to make changes to the product(s) or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Wireless Made Simple is a registered trademark of Linx Acquisitions LLC. LoRaWAN is a registered trademark of Semtech Corporation. Sigfox is a registered trademark of SIGFOX. Other product and brand names may be trademarks or registered trademarks of their respective owners.

Copyright © 2020 Linx Technologies

All Rights Reserved







Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Linx Technologies: ADP-SMAM-SMBF-G