



Spec No. :DS22-2012-0082 Effective Date: 05/29/2019

Revision: G

LITE-ON DCC

RELEASE

BNS-OD-FC001/A4



1. Description

SMD LEDs from Lite-On are available in miniature sizes and special configurations for automated PC board assembly and space-sensitive applications. These SMD LEDs are suitable for use in a wide variety of electronic equipment, including cordless and cellular phones, notebook computers, network systems, home appliances, and indoor signboard applications.


1.1 Features


- Meet ROHS
- Package in 12mm tape on 7" diameter reels
- EIA STD package
- I.C. compatible
- Compatible with automatic placement equipment
- Compatible with infrared reflow solder process
- Preconditioning: accelerate to JEDEC level 3


1.2 Applications


- Telecommunication, Office automation, home appliances, industrial equipment
- Status indicator
- Signal and Symbol Luminary
- Front panel backlighting

2. Package Dimensions









Part No.	Lens Color	Source Color	Pin Assignment
		InGaN Blue	(0,1) , 2
LTST-008BGEW	White Diffused	InGaN Green	3,4
		AllnGaP Red	5 , (6,7)

Notes:

- 1. All dimensions are in millimeters.
- 2. Tolerance is ±0.1 mm (.004") unless otherwise noted.




3. Rating and Characteristics

3.1 Absolute Maximum Ratings at Ta=25℃

Parameter		Unit		
Farameter	Blue	Green	Red	
Power Dissipation	80	80	72	mW
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100	100	80	mA
DC Forward Current	20	20	30	mA
Operating Temperature Range	-40℃ to + 85℃			
Storage Temperature Range	-40℃ to + 100℃			

3.2 Suggest IR Reflow Condition for Pb Free Process:

IR-Reflow Soldering Profile for lead free soldering (Acc. to J-STD-020B)





3.3 Electrical / Optical Characteristics at Ta=25℃

Parameter	Comple at		LTST-	008BGEW	Test Condition	Unit.	
	Symbol		Blue	Green	Red	rest Condition	Onit.
		Min.	0.34	1.25	0.76		
Luminous Flux ¹	$\Phi_{\rm v}$	Тур.	-	-	-	I _F = 20mA Note 1	lm
		Max.	0.84	2.13	2.13		
		Min.	112	450	280		
Luminous Intensity	IV	Тур.	-	-	-	IF = 20mA Note 2	mcd
		Max.	280	900	710		
Viewing Angle	201/2	Тур.		130		Note 3 (Fig.5)	deg
Peak Emission Wavelength	λP	Тур.	468	518	632	Measurement @Peak (Fig.1)	nm
		Min.	465	520	-	IF = 20mA Note 4	nm
Dominant Wavelength ⁴	$\lambda_{ m d}$	Тур	-	-	624		
		Max.	475	535	-		
Spectral Line Half-Width	Δλ	Тур.	25	35	20	IF = 20mA	nm
		Min.	2.8	2.8	1.8		
Forward Voltage	V _F	Тур.	-	-	-	IF = 20mA	V
		Max.	3.6	3.6	2.4		
Reverse Current	IP	Mari 40	IR Max. 10 10	40	10	V _R = 5V	μ A
Neverse Current	IR	IVIAX.	10	10	10	Note 5	μΑ

Notes:

- Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
- 2. Luminous Intensity (mcd) is for reference.
- 3. θ 1/2 is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- 4. The dominant wavelength, λd is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.
- 5. Reverse voltage (VR) condition is applied to IR test only. The device is not designed for reverse operation.



4. Bin Code List

4.1 VF Rank

Forward Vol	tage Color : <u>Blue</u> , Uni	t : V @20mA
Bin Code	Min.	Max.
D7	2.8	3.0
D8	3.0	3.2
D9	3.2	3.4
D10	3.4	3.6

Tolerance on each Forward Voltage bin is +/-0.1 volt

Forward Volt	age Color : <u>Green</u> , Un	it : V @20mA
Bin Code	Min.	Max.
D7	2.8	3.0
D8	3.0	3.2
D9	3.2	3.4
D10	3.4	3.6

Tolerance on each Forward Voltage bin is +/-0.1 volt

Forward Vo	ltage Color : <u>Red</u> , Uni	t : V @20mA
Bin Code	Min.	Max.
D2	1.8	2.0
D3	2.0	2.2
D4	2.2	2.4

Tolerance on each Forward Voltage bin is +/-0.1 volt



4.2 IV Rank

Lumin	ous Spec.	Color : <u>Blue</u>	@20mA		
Bin Code	Luminous	Flux (Im)	Luminous Intensity (mcd)		
Bill Code	Min.	Max.	Min.	Max.	
С	0.34	0.54	112	180	
D	0.54	0.84	180	280	

Tolerance on each Luminous bin is +/- 10%, and Luminous Intensity(mcd) is for reference.

Luminous II	ntensity (Color : <u>Green</u>	@ 20mA		
Bin Code	Luminous	s Flux (Im)	Luminous Intensity (mcd)		
Bin Code	Min.	Max.	Min.	Max.	
F	1.25	2.13	450	710	

Tolerance on each Luminous bin is +/- 10%, and Luminous Intensity(mcd) is for reference.

Luminous Intensity		Color : <u>Red</u>	@ 20mA		
Pin Codo	Luminous	Flux (Im)	Luminous Intensity (mcd)		
Bin Code	Min.	Max.	Min.	Max.	
Е	0.76	1.35	280	450	
F	1.35	2.13	450	710	

Tolerance on each Luminous bin is +/- 10%, and Luminous Intensity(mcd) is for reference.



4.3 Bin Code on Tag Cross Table

Forward Voltage Unit : V @ 20mA							
D's Os Is Os Tax	Blue		Gr	een	R	ed	
Bin Code On Tag	Code	Range	Code	Range	Code	Range	
A1					D2	1.8-2.0	
A2			D7	2.8-3.0	D3	2.0-2.2	
А3					D4	2.2-2.4	
A4					D2	1.8-2.0	
A5			D8	3.0-3.2	D3	2.0-2.2	
A6	D7	2.8-3.0			D4	2.2-2.4	
A7	DΊ				D2	1.8-2.0	
A8			D9	3.2-3.4	D3	2.0-2.2	
A9					D4	2.2-2.4	
A10			D10	3.4-3.6	D2	1.8-2.0	
A11					D3	2.0-2.2	
A12					D4	2.2-2.4	
B1				2.8-3.0	D2	1.8-2.0	
B2			D7		D3	2.0-2.2	
В3					D4	2.2-2.4	
B4					D2	1.8-2.0	
B5			D8	3.0-3.2	D3	2.0-2.2	
B6					D4	2.2-2.4	
В7	D8	3.0-3.2			D2	1.8-2.0	
B8			D9	3.2-3.4	D3	2.0-2.2	
В9					D4	2.2-2.4	
B10					D2	1.8-2.0	
B11			D10	3.4-3.6	D3	2.0-2.2	
B12			2.0		D4	2.2-2.4	



Forward Voltage Unit : V @ 20mA								
Bin Code On Ton	ВІ	ue	Gre	Green		ed		
Bin Code On Tag	Code	Range	Code	Range	Code	Range		
C1					D2	1.8-2.0		
C2			D7	2.8-3.0	D3	2.0-2.2		
C3					D4	2.2-2.4		
C4					D2	1.8-2.0		
C5			D8	3.0-3.2	D3	2.0-2.2		
C6	D9	3.2-3.4			D4	2.2-2.4		
C7	Da				D2	1.8-2.0		
C8					D9	3.2-3.4	D3	2.0-2.2
C9					D4	2.2-2.4		
C10					D2	1.8-2.0		
C11			D10	3.4-3.6	D3	2.0-2.2		
C12					D4	2.2-2.4		
D1					D2	1.8-2.0		
D2				D7	2.8-3.0	D3	2.0-2.2	
D3								
D4					D2	1.8-2.0		
D5			D8	3.0-3.2	D3	2.0-2.2		
D6	D10	3.4-3.6			D4	2.2-2.4		
D7	D10	J. T -J.U			D2	1.8-2.0		
D8			D9	3.2-3.4	D3	2.0-2.2		
D9		-			D4	2.2-2.4		
D10					D2	1.8-2.0		
D11			D10	3.4-3.6	D3	2.0-2.2		
D12					D4	2.2-2.4		

	Luminous Spec.		Unit : Im @20mA								
h and the state of		ue Green		een	Red						
Bin Code	Code	Range	Code	Range	Code	Range					
E1	C	0.34-0.54	0.34-0.54	0.34-0.54	0.34-0.54				E	0.76-1.35	
E2	C						F	1.25-2.13	F	1.35-2.13	
E3	D 054094	D 0.54.0.94	0.54.0.94	0.54.0.04	0.54.0.04	0.54.0.04	0.54.0.94	D 0.54-0.84	1.20-2.13	Е	0.76-1.35
E4	U	0.54-0.64			F	1.35-2.13					



5. Typical Electrical / Optical Characteristics Curves.

(25℃ Ambient Temperature Unless Otherwise Noted)




Fig.1 RELATIVE INTENSITY VS. WAVELENGTH




Fig.2 FORWARD CURRENT VS. FORWARD VOLTAGE




Fig.4 RELATIVE LUMINOUS
INTENSITY VS. FORWARD CURRENT




Fig.3 FORWARD CURRENT
DERATING CURVE




Fig.5 Spatial Distribution




6. User Guide


6.1 Cleaning

Do not use unspecified chemical liquid to clean LED they could harm the package. If cleaning is necessary, immerse the LED in ethyl alcohol or isopropyl alcohol at normal temperature for less one minute.

6.2 Recommend Printed Circuit Board Attachment Pad



6.3 Package Dimensions of Tape And Reel




Note:

1. All dimensions are in millimeters (inches).



6.4 Package Dimensions of Reel



Notes:

- 1. Empty component pockets sealed with top cover tape.
- 2. 7 inch reel 3000 pieces per reel.
- 3. Minimum packing quantity is 500 pieces for remainders.
- 4. The maximum number of consecutive missing lamps is two.
- 5. In accordance with EIA-481-1-B specifications.

Part No. : LTST-008BGEW BNS-OD-FC002/A4



7. Cautions

7.1 Application

The LEDs described here are intended to be used for ordinary electronic equipment (such as office equipment, communication equipment and household applications). Consult Liteon's Sales in advance for information on applications in which exceptional reliability is required, particularly when the failure or malfunction of the LEDs may directly jeopardize life or health (such as in aviation, transportation, traffic control equipment, medical and life support systems and safety devices).

7.2 Storage

The package is sealed:

The LEDs should be stored at 30℃ or less and 70%RH or less. And the LEDs are limited to use within one year, while the LEDs is packed in moisture-proof package with the desiccants inside.

The package is opened:

The storage ambient for the LEDs should not exceed 30°C temperature and 60% relative humidity.

It is recommended that LEDs out of their original packaging are IR-reflowed within 168hrs.

For extended storage out of their original packaging, it is recommended that the LEDs be stored in a sealed container with appropriate desiccant, or in a desiccators with nitrogen ambient.

LEDs stored out of their original packaging for more than 168hrs should be baked at about 60 $^{\circ}$ C for at least 48 hours before solder assembly.

7.3 Cleaning

Use alcohol-based cleaning solvents such as isopropyl alcohol to clean the LED if necessary.

7.4 Soldering

Recommended soldering conditions:

Reflow soldering		Soldering iron	
Pre-heat	150~200℃	Temperature	300℃ Max.
Pre-heat time	120 sec. Max.	Soldering time	3 sec. Max.
Peak temperature	260℃ Max.		(one time only)
Soldering time	10 sec. Max.(Max. two times)		

Notes:

Because different board designs use different number and types of devices, solder pastes, reflow ovens, and circuit boards, no single temperature profile works for all possible combinations.

However, you can successfully mount your packages to the PCB by following the proper guidelines and PCB-specific characterization.

LITE-ON Runs both component-level verification using in-house **KYRAMX98** reflow chambers and board-level assembly. The results of this testing are verified through post-reflow reliability testing. Profiles used at LITE-ON are based on JEDEC standards to ensure that all packages can be successfully and reliably surface mounted.

Figure on page3 shows a sample temperature profile compliant to JEDEC standards. You can use this example as a generic target to set up your reflow process. You should adhere to the JEDEC profile limits as well as specifications and recommendations from the solder paste manufacturer to avoid damaging the device and create a reliable solder joint.





7.5 Drive Method

A LED is a current-operated device. In order to ensure intensity uniformity on multiple LEDs connected in parallel in an application, it is recommended that a current limiting resistor be incorporated in the drive circuit, in series with each LED as shown in Circuit A below.

Circuit model A

Circuit model B





- (A) Recommended circuit.
- (B) The brightness of each LED might appear different due to the differences in the I-V characteristics of those LEDs.

7.6 ESD (Electrostatic Discharge)

Static Electricity or power surge will damage the LED. Suggestions to prevent ESD damage:

- Use of a conductive wrist band or anti-electrostatic glove when handling these LEDs.
- All devices, equipment, and machinery must be properly grounded.
- Work tables, storage racks, etc. should be properly grounded.
- Use ion blower to neutralize the static charge which might have built up on surface of the LED's plastic lens as a result of friction between LEDs during storage and handling.

ESD-damaged LEDs will exhibit abnormal characteristics such as high reverse leakage current, low forward voltage, or "no lightup" at low currents.

To verify for ESD damage, check for "lightup" and Vf of the suspect LEDs at low currents.

The Vf of "good" LEDs should be >2.0V@0.1mA for InGaN product and >1.4V@0.1mA for AllnGaP product.



8. Reliability Test

No.	Test item	Test condition	Reference standard
1	Resistance to soldering heat	Tsld = 260℃, 10sec. 3 times	JEITA ED-4701 300 301
2	Solderability	Tsld= $245\pm5\%$ (Lead Free Solder, Coverage \geq 95% of the dipped surface)	JEITA ED-4701 300 303
3	Thermal Shock	85 ± 5℃ ~ -30℃ ± 5℃ 30min 30min 100cycles	JEITA ED-4701 300 307
4	Temperature Cycle	-55℃ ~ 25℃ ~ 100℃ ~ 25℃ 30min 5min 30min 5min 100cycles	JEITA ED-4701 100 105
5	High Temperature Storage	100℃ 1000hrs	JEITA ED- 4701 200 201
6	Low Temperature Storage	-55℃ 1000hrs	JEITA ED-4 701 200 202
7	Temperature Humidity Storage	60℃/90%RH 300hrs	JEIT A ED-4701 100 103
8	Room temp life test	25℃, IF: Max current , 1000hrs	
9	High temp life test	85℃, IF: For derating curve 1000hrs	
10	Low temp life test	-30℃, IF: Typical current 1000hrs	JEITA ED-4701 200 202
11	High Temp./Humidity life test (WHTOL)	60°C 90%RH IF: For derating curve 1000hrs	

9. Others

The appearance and specifications of the product may be modified for improvement without prior notice.



10. Suggested Checking List

Training and Certification

- 1. Everyone working in a static-safe area is ESD-certified?
- 2. Training records kept and re-certification dates monitored?

Static-Safe Workstation & Work Areas

- 1. Static-safe workstation or work-areas have ESD signs?
- 2. All surfaces and objects at all static-safe workstation and within 1 ft measure less than 100V?
- 3. All ionizer activated, positioned towards the units?
- 4. Each work surface mats grounding is good?

Personnel Grounding

- 1. Every person (including visitors) handling ESD sensitive (ESDS) items wears wrist strap, heel strap or conductive shoes with conductive flooring?
- 2. If conductive footwear used, conductive flooring also present where operator stand or walk?
- 3. Garments, hairs or anything closer than 1 ft to ESD items measure less than 100V*?
- 4. Every wrist strap or heel strap/conductive shoes checked daily and result recorded for all DLs?
- 5. All wrist strap or heel strap checkers calibration up to date?

Note: *50V for InGaN LED.

Device Handling

- 1. Every ESDS items identified by EIA-471 labels on item or packaging?
- 2. All ESDS items completely inside properly closed static-shielding containers when not at static-safe workstation?
- 3. No static charge generators (e.g. plastics) inside shielding containers with ESDS items?
- 4. All flexible conductive and dissipative package materials inspected before reuse or recycles?

Others

- 1. Audit result reported to entity ESD control coordinator?
- 2. Corrective action from previous audits completed?
- 3. Are audit records complete and on file?

Part No. : LTST-008BGEN BNS-OD-FC002/A4

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

LITEON:

LTST-008BGEW