		2			
		1 NO COMPONEN	IT NO DESCRIPTIC	DN QTY/M U/M	
BILL OF MATERIAL					
<∅.640±.010>					
- 0.038+ 010			HERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.		
<Ø.938±.010>			DENOTES CPK DIMENSIONS,-MINIMUM CPK VALUE		
NOTE: MATERIAL: BLACK, OIL RESISTANT, SYNTHETIC RUBBER SHEET, 75/85 DUROMETER. FLAT SURFACES			DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS. DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE, WITHIN THE DIMENSIONAL LIMITATIONS		
TO BE SMOOTH & FRI FLAWS.	CP MU	SHOWN ON DRAWING AND INITIALLY LOCATED TO			
	E FR	COPIES TO M	ATL SPEC	FINISH	
	NEW 4	1 9 18 DI 2 10 19	RW KAM DATE 12/1	0/97 SCALE 4:1	
			HK DATE	SUPER DRW	
	CTURS CTURS	4 13 21 5 14 23 A	PPD DATE	RAW STK WT	
	(120) (120) (120)	6 15 33 -	TOLERANCE UNLESS OT	HERWISE SPECIFAED	
	1.30/98/	7 16 43 TWO PLACE DEC ±.01 FRACTION			
	J. J. SO J PR NU IN KAM	TITLE	WASHE	ANGLAA FFI	
	CH C				
	APD	DES PLAINES,		-901-074	

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Littelfuse:

901-074