

313/315 Series Lead-Free 3AG, Slo-Blo® Fuse



**Description**

The 3AG Slo-Blo® fuse solves a broad range of application requirements while offering reliable performance and cost-effective circuit protection.

The fuse catalog number with the suffix "ID" instantly identifies itself upon opening by showing a discoloration of its glass body. Guesswork and time consuming circuit testing are eliminated. This unique design offers the same quality performance characteristics as the standard 3AG Slo-Blo® Fuse design.

**Agency Approvals**

Agency	Agency File Number	Ampere Range
	E10480	0.010A - 10A**
	29862	0.010A - 10A**/15A**
	E10480	10A - 30A
	313 Series (Cartridge): NBK060618-E10480A NBK060618-E10480C	1-5A 6.25- 10A**
	315 Series (Leaded): NBK060618-E10480B NBK060618-E10480D	1-5A 6.25-10A**
	SU05001-6004	2.25-2.5A
	SU05001-5007	2.8A - 3.2A
	SU05001-5008	4A - 6.3A
	SU05001-5009	7A-8A
	N/A	0.010A - 10A**/15A**

\*\* See note under Electrical Characteristics by item

**Features**

- Conforms to UL/CSA/ NMX 248-1 and UL/CSA/ NMX 248-14
- Available in cartridge and axial lead format and with various forming dimensions
- RoHS compliant and Lead-free
- Conforms to DENAN's Appendix 3

**Applications**

Used as supplementary protection in appliance or utilization equipment to provide individual protection for components or internal circuits.

**Additional Information**



**Datasheet  
313 Series**



**Resources  
313 Series**



**Samples  
313 Series**



**Accessories  
313 & 315 Series**



**Datasheet  
315 Series**



**Resources  
315 Series**



**Samples  
315 Series**

For recommended fuse accessories for this product series, see '[Recommended Accessories](#)' section.

**Electrical Characteristics by Series**

% of Ampere Rating	Ampere Rating	Opening Time
100%	10mA – 30A	4 hours, Minimum
135%	10mA – 30A	1 hour, Maximum
200%	10mA – 15A	5 sec., Min., 30 sec., Max
	20A – 30A	5 sec., Min., 60 sec Max


### Electrical Characteristic Specifications by Item

Amp Code	Ampere Rating (A)	Voltage Rating (V)	Interrupting Rating	Nominal Cold Resistance (Ohms)	Nominal Melting I <sup>2</sup> t (A <sup>2</sup> sec)	Agency Approvals					
						UL	SR	CCC	RU	PS E	CE
0.01	0.01	250	35A@250Vac 10KA@125Vac	4300.0000	0.000121	x	x	-	-	-	x
0.031	0.031	250		430.0000	0.00303	x	x	-	-	-	x
0.04	0.04	250		300.0000	0.00630	x	x	-	-	-	x
0.062	0.062	250		120.0000	0.0210	x	x	-	-	-	x
0.1	0.1	250		43.0000	0.0850	x	x	-	-	-	x
0.125	0.125	250		30.0000	0.152	x	x	-	-	-	x
0.15	0.15	250		20.0000	0.270	x	x	-	-	-	x
0.175	0.175	250		8.6700	0.177	x	x	-	-	-	x
0.187	0.187	250		8.0100	0.230	x	x	-	-	-	x
0.2	0.2	250		6.5900	0.270	x	x	-	-	-	x
0.25	0.25	250		4.2700	0.385	x	x	-	-	-	x
0.3	0.3	250		3.1350	0.730	x	x	-	-	-	x
0.375	0.375	250		2.0950	1.23	x	x	-	-	-	x
0.4	0.4	250		1.8750	1.35	x	x	-	-	-	x
0.5*	0.5	250		1.2600	2.55	x	x	-	-	-	x
0.6	0.6	250		0.9120	4.00	x	x	-	-	-	x
0.7	0.7	250		0.7000	5.90	x	x	-	-	-	x
0.75	0.75	250		0.6215	7.16	x	x	-	-	-	x
0.8	0.8	250		0.5540	8.00	x	x	-	-	-	x
1.0*	1	250		0.3750	14.0	x	x	-	-	x	x
1.2	1.2	250		0.2780	21.5	x	x	-	-	x	x
1.25	1.25	250		0.2600	24.0	x	x	-	-	x	x
1.5*	1.5	250		0.1910	38.0	x	x	-	-	x	x
1.6	1.6	250		0.1710	49.6	x	x	-	-	x	x
1.8	1.8	250		0.1410	92.0	x	x	-	-	x	x
2.0*	2	250	0.1169	77.0	x	x	-	-	x	x	
2.25	2.25	250	0.0968	121	x	x	x	-	x	x	
2.5	2.5	250	0.0811	199	x	x	x	-	x	x	
2.8	2.8	250	0.0675	269	x	x	x	-	x	x	
3.*	3	250	0.0593	200	x	x	x	-	x	x	
3.2	3.2	250	0.0529	209	x	x	x	-	x	x	
4.0*	4	250	0.0311	76.1	x	x	x	-	x	x	
5.0*	5	250	0.0214	276	x	x	x	-	x	x	
6.25*	6.25	250	0.0154	388	x	x	x	-	x	x	
6.3	6.3	250	0.0154	388	x	x	x	-	x	x	
7.0*	7	250	0.0128	547	x	x	x	-	x	x	
8.0*	8	250	0.0111	701	x	x	x	-	x	x	
10.0**	10	250	0.0083	1285	x	x	-	-	x	x	
10.0*	10	32	0.0083	1285	-	-	-	x	-	-	
12.0	12	32	0.0065	1200	-	-	-	x	-	-	
15.0	15	32	0.0050	2650	-	-	-	x	-	-	
20.0	20	32	0.0022	9560	-	-	-	x	-	-	
25.0	25	32	0.0017	16500	-	-	-	x	-	-	
30.0	30	32	0.0012	26900	-	-	-	x	-	-	

\* For 313series, these ratings available with an indicating option. Add the "ID" designation to the series number. i.e. 313.500ID.

\*\* The 10A and 15A ratings are ratings are designed for special voltage requirement. For 10A, it is available as 250Vac rated and the part number is 0313010.MX250P


**Temperature Re-rating Curve**




**A - For 313/315 Series, from 10mA to 150mA**  
**B - For all other ampere ratings of 313/315 series**

**Note:**  
Rerating depicted in this curve is in addition to the standard derating of 25% for continuous operation.

**Average Time Current Curves**



**Soldering Parameters - Wave Soldering**



**Recommended Process Parameters:**

Wave Parameter	Lead-Free Recommendation
Preheat: (Depends on Flux Activation Temperature)	(Typical Industry Recommendation)
Temperature Minimum:	100°C
Temperature Maximum:	150°C
Preheat Time:	60-180 seconds
Solder Pot Temperature:	260°C Maximum
Solder Dwell Time:	2-5 seconds

**Recommended Hand-Solder Parameters:**

Solder Iron Temperature: 350°C +/- 5°C  
Heating Time: 5 seconds max.

**Note: These devices are not recommended for IR or Convection Reflow process.**

**Packaging**


Packaging Option	Packaging Specification	Quantity	Quantity & Packaging Code	Taping Width
<b>313 Series</b>				
Bulk	N/A	1000	MX	N/A
Bulk	N/A	100	HX	N/A
<b>315 Series</b>				
Bulk	N/A	1000	MX	N/A
Bulk	N/A	100	HX	N/A
Bulk	N/A	1000	MXB	N/A

### Product Characteristics

<b>Materials</b>	Body: Glass Cap: Nickel-plated brass Leads: Tin-plated Copper
<b>Terminal Strength</b>	MIL-STD-202, Method 211, Test Condition A
<b>Solderability</b>	MIL-STD-202 method 208
<b>Product Marking</b>	Cap1: Brand logo, current and voltage ratings Cap2: Series and agency approval marks


<b>Operating Temperature</b>	-60°C to +125°C
<b>Thermal Shock</b>	MIL-STD-202, Method 107, Test Condition B: (5 cycles -65°C to +125°C)
<b>Vibration</b>	MIL-STD-202, Method 201
<b>Humidity</b>	MIL-STD-202, Method 103, Test Condition A: High RH (95%) and Elevated temperature (40°C) for 240 hours
<b>Salt Spray</b>	MIL-STD-202, Method 101, Test Condition B

### Dimensions



Measurements displayed in millimeters (inches)

### Part Numbering System



### Recommended Accessories

Accessory Type	Series	Description	Max Application Voltage	Max Application Amperage
Holder	<a href="#">155100</a>	Twist-Lock In-Line Fuseholder	32	20
	<a href="#">342</a>	Traditional Panel Mount Fuseholder	250	20
	<a href="#">346</a>	Panel Mount Flip-Top Shock-Safe Fuseholder	250	15
	<a href="#">345</a>	Shock-Safe Fuseholder with PC Mount, Solder Mount and Panel Mount options	250	16
Block	<a href="#">354</a>	Low Profile OMNI-BLOK® Fuse Block	600	30
	<a href="#">359</a>	High Current Screw Terminal Fuse Block		30
Clip	<a href="#">122</a>	High Current Traditional PC Board Fuse Clip	1000	30
	<a href="#">101</a>	Rivet/Eyelet Type Fuse Clip	1000	15

**Notes:**

- Do not use in applications above rating.
- Please refer to fuseholder data sheet for specific re-rating information.
- Please contact factory for applications greater than the max voltage and amperage shown.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Littelfuse:

[0375012.MXP](#) [0375012.HXP](#) [0375015.HXP](#) [0315020.MXBP](#) [313005P](#) [0313.031HXP](#) [0313.040MXP](#) [0313001.H](#)  
[0313015.H](#) [031506.3MXP](#) [0313.250H](#) [0313.600HXP](#) [0313010.HXP](#) [0313.150HXP](#) [0313015.M](#) [0315010.MXP](#)  
[0313.375M](#) [0313.800H](#) [0313003.HXP](#) [0313005.H](#) [031301.5HXP](#) [0313001.M](#) [0315008.MXP](#) [031302.5H](#)  
[031501.8HXP](#) [0313001.HXP](#) [031501.2HXP](#) [031306.3M](#) [0315003.MXP](#) [0315.100MXP](#) [0313.700HXP](#) [0313015.HXP](#)  
[0313025.M](#) [0315.031HXP](#) [0313.700H](#) [031301.2M](#) [03152.25MXP](#) [031501.5HXP](#) [0313.125M](#) [0313008.HXID](#)  
[0313.800MXP](#) [031502.8HXP](#) [0313.100MXP](#) [0313.300H](#) [0313.750MXP](#) [031301.5M](#) [03132.25HXP](#) [0313005.HXID](#)  
[0313.010MXP](#) [0313.300M](#) [031302.8MXP](#) [0313025.HXP](#) [031301.5HXID](#) [0315.200MXP](#) [0313.375H](#) [0313015.MXP](#)  
[0313010.H](#) [0313.600M](#) [03136.25H](#) [031502.5MXP](#) [0313.100H](#) [0313.187M](#) [0315.800HXP](#) [0315012.MXP](#)  
[0313003.MXP](#) [03156.25MXP](#) [0313.125H](#) [0313.600H](#) [0315010.HXP](#) [0313.400HXP](#) [031301.8H](#) [031302.5M](#)  
[0313.100M](#) [0315.150MXP](#) [0315015.HXP](#) [0315.250MXP](#) [0313002.H](#) [0315.150HXP](#) [0315003.HXP](#) [0313002.HXID](#)  
[0313005.M](#) [0313.150MXP](#) [0313020.HXP](#) [0315.300MXP](#) [0315.700MXP](#) [0313.800M](#) [0313.125MXP](#) [0313.375MXP](#)  
[0313007.M](#) [031303.2M](#) [031301.6M](#) [0315.500MXP](#) [0313.250M](#) [0313.100HXP](#) [031306.3MXP](#) [03136.25HXID](#)  
[0315020.HXP](#) [031503.2HXP](#) [03152.25HXP](#) [0315030.HXP](#)