POWR-BAR Distribution









NGTH mm) 60 79 106



Description

A key objective for panel designers is safe distribution of power to multiple fuse holders in a compact design. The Littelfuse UL 508 Listed bus bar system eliminates most wire terminations in a timesaving package. A power distribution block and associated conductors are no longer needed to feed multiple POWR-SAFE fuse holders.

Features/Benefits

- Touch-safe design offers protection when replacing fuses
- Compact design
- 35 mm DIN-rail mountable
- Available in one and three phase configurations
- Can be cut down to optimal size

Recommended Fuse Holders

LFPSC Series LPSC / LPSM Series (600 V) LPHV Series (1000 V)

Web Resources

Download technical information: littelfuse.com/busbar

Specifications

Voltage Ratings 600 V ac/dc 1000 V dc*

Current Ratings

CROSS SECTION (mm²)	18 mm ²	25 mm ²
END FED	80 A	100 A
CENTER FED	160 A	200 A

SCCR 10 kA, 100 kA[†] Conductor Copper Pitch 17.8 mm

UL 508 Listed (File E328654) **Approvals** RoHS Compliant, Lead (Pb) free **Environmental**

- *1 Phase 18 mm² rated 1000 VDC up to 160 A when center fed
- 1 Phase 25 mm² rated 1000 VDC up to 200 A when center fed [†]When protected directly upstream by Class J 175 amperes max (18 mm² bus bar) and Class J 200 amperes max (25 mm² bus bar).

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/ product-disclaimer.

Ordering Information

1 PHASE, 18 mm ²		LENGTH		1 PHASE, 25 n	LENGT		
	ORDERING NUMBER	POLES	(mm)		ORDERING NUMBER	POLES	(mm)
	1PH3P18mm	3	60		1PH3P25mm	3	60
	1PH4P18mm	4	79		1PH4P25mm	4	79
	1PH6P18mm	6	106		1PH6P25mm	6	106
	1PH9P18mm	9	159		1PH9P25mm	9	159
	1PH12P18mm	12	212		1PH12P25mm	12	212
	1PH15P18mm	15	272		1PH15P25mm	15	272
	1PH57P18mm	57	1009		1PH57P25mm	57	1009

3 PHASE, 18 n	LENGTH	
ORDERING NUMBER	POLES	(mm)
3PH6P18mm	6	104
3PH9P18mm	9	158
3PH12P18mm	12	214
3PH15P18mm	15	266
3PH21P18mm	21	374
3PH27P18mm	27	481
3PH33P18mm	33	586
3PH39P18mm	39	693
3PH57P18mm	57	1009

3 PHASE, 25 n	LENGTH	
ORDERING NUMBER	POLES	(mm)
3PH6P25mm	6	104
3PH9P25mm	9	158
3PH12P25mm	12	214
3PH15P25mm	15	266
3PH57P25mm	57	1009


Endcaps are standard with all 3 phase configurations except 57-pole. Endcaps are not needed for the 1 phase configurations from the factory or if the copper bus is trimmed per the supplied instructions. Power feed lugs and protective covers are extra.

Accessories

Power Feed Lug


PART NUMBER	WIRERANGE	WIRE TYPE	TORQUE	PHASE	FUSE HOLDER
BB17	#10 - 1/0 AWG	CU	50 lb-in	Single	LPSM/LPSC/LPHV
BB18	#10 - 1/0 AWG	CU	50 lb-in	Three	LPSM/LPSC
BB19	#10 - 1/0 AWG	CU	50 lb-in	Single	LFPSM/LFPSC
BB20	#10 - 1/0 AWG	CU	50 lb-in	Three	LFPSM/LFPSC

Power Feed Lugs are 115A 1000V AC/DC rated









Endcaps

PART NUMBER	PHASE	QUANTITY
EDCP42	Single	50
EDCP7	Three	50





Pole Protective Covers

PART NUMBER	QUANTITY
CTPT5	5





Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Littelfuse:

1PH12P25MM 1PH9P25MM 1PH15P18MM 1PH3P25MM 1PH3P18MM 1PH6P18MM 1PH5PP18MM
1PH9P18MM 1PH6P25MM 1PH12P18MM 1PH5P25MM 1PH15P25MM 3PH6P25MM 3PH15P25MM EDCP7
3PH6P18MM 3PH9P18MM 3PH15P18MM EDCP42 3PH57P18MM 3PH12P25MM 3PH9P25MM BB18
3PH57P25MM BB19 1PH4P25MM BB17 3028-2 BB21 10631800 BB22 02020500 03531100 12450100
12540300 19805400 12530300 12540200 913-007-R 913-008-R 06092600 07291700 02010300 07290900
10823100-FCB 00517900 10821200 07290700 10823300-FCB 10753900 10843500 07290100 07290800
00607260 03530900 07290200 03520100 03531000 07290500 07395200 10630100 10631700 00604900-WBG
07290600 10821100 10823100 00517800 00680400-WBG 07294000 10823300 10843560