

Thermistor Probes and Assemblies Straight

USP7806 Thermistor Probe



Description


Littelfuse offers Stainless probe assemblies suitable for a wide range of temperature sensing applications. If the dimensions and electrical characteristics on this product won't work for your requirements, please contact us for further assistance.


Features

- PFA Insulated Lead Wire
- 150°C Max Operating Temperature

Dimensions

Part Numbering System





Note: Not all combinations of Part Number codes are available. Contact Littelfuse for details.

Dimensions in inches.

А	В	С	D
0.250" ± 0.090" Strip	12.0" ± 1.0"	1.500" ± 0.075"	0.125" ± 0.005"

Specifications

Part Number	Resistance Ohms @25°C	Resistance Tol. ± % @ 25°C	R-T Curve	Temperature Coefficient (% / °C) @ 25°C	Temperature Rating (°C)
USP7806	100000	4.78	V	-4.78	-55 to +150

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littlefuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: www.littlefuse.com/disclaimer-electronics

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Littelfuse: USP7806