



UNCONTROLLED DOCUMENT

PART NUMBER

LCM-S01602DSR-2K

REV.



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.=+0.00 DECIMAL PRECISION MAX.=+0.00 DECIMAL PRECISION

REV.

PART NUMBER

LCM-S01602DSR-2K

16 x 2 LCD MODULE, STN GRAY, REFLECTIVE,
12:00 VIEW, 1/16 DUTY, 1/5 BIAS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

LUMEX
INCORPORATED

290 E. HELLEN ROAD
PALATINE, ILLINOIS 60067
PHONE: (847) 359-2790
WEB: <http://www.lumex.com>

DRAWN BY:

SA/BC

CHECKED BY:

APPROVED BY:

DATE: 4-17-00

PAGE: 1 OF 2


SCALE: N/A

PIN CONFIGURATION

PIN NO.	SYMBOL	LEVEL	FUNCTION
1	V _{SS}	-	POWER SUPPLY
2	V _{DD}	-	
3	V _O	-	
4	RS	H/L	REGISTER SELECT SIGNAL H: DATA INPUT L: INSTRUCTION INPUT
5	R/W	H/L	H: DATA READ (MODULE-->MPU) L: DATA WRITE (MODULE<--MPU)
6	E	H,H->L	READ WRITE ENABLE
7~14	DB0~DB7	H/L	DATA BUS-SOFTWARE SELECTABLE 4 OR 8 BIT MODE.

CAUTION: STATIC SENSITIVE DEVICE
FOLLOW PROPER E.S.D. HANDLING PROCEDURES
WHEN WORKING WITH THIS PART.

CHARACTER DETAIL



ELECTRICAL CHARACTERISTICS

V_{DD}=4.5V to 5.5V, T_A=-30°C TO +85°C

ITEM	SYMBOL	CONDITION	STANDARD VALUE			UNIT
			MIN.	TYP.	MAX.	
OPERATING VOLTAGE	V _{DD}	-	4.5	-	5.5	V
INPUT VOLTAGE 1	HIGH	V _{IH1}	-	2.2	-	V _{DD}
	LOW	V _{IL1}	-	-0.3	-	0.6
INPUT VOLTAGE 2	HIGH	V _{IH2}	-	V _{DD} -1.0	-	V _{DD}
	LOW	V _{IL2}	-	-0.2	-	1.0
OUTPUT VOLTAGE	HIGH	V _{OH}	I _{OH} =0.205mA	2.4	-	V
	LOW	V _{OL}	I _{OL} =1.2mA	-	-	0.4
INPUT LEAKAGE CURRENT	I _{LKG}	V _{IN} =0 OR V _{DD}	-	-	1.0	μA
INPUT LOW CURRENT	I _{IL}	V _{DD} =5V	-50	-125	-250	μA
EXTERNAL CLOCK FREQUENCY	f _{EC}	-	125	250	350	kHz
EXTERNAL CLOCK DUTY	duty	-	45	50	55	%
EXTERNAL CLOCK RISE TIME	t _R	-	-	-	0.2	μs
EXTERNAL CLOCK FALL TIME	t _F	-	-	-	0.2	μs
INTERNAL CLOCK FREQUENCY	f _{osc1}	R _f =91kΩ ±2%	190	270	255	kHz
LCD DRIVING VOLTAGE	V _{LCD}	1/5 BIAS	4.6	-	10.0	V

ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	TEST CONDITION	STANDARD VALUE		UNIT
			MIN	MAX	
SUPPLY VOLTAGE FOR LOGIC	V _{DD}	T _a =25°C	-0.3	7.0	V
SUPPLY VOLTAGE FOR LCD DRIVE	V _{LCD}	-	V _{DD} -15	V _{DD} +0.3	V
INPUT VOLTAGE	V _I	T _a =25°C	-0.3	V _{DD} +0.3	V
OPERATING TEMPERATURE	T _{opr}	-	0	50	°C
STORAGE TEMPERATURE	T _{stg}	-	-20	70	°C

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.=+0.00 DECIMAL PRECISION MAX.=+0.00 DECIMAL PRECISION

REV.

PART NUMBER

LCM-S01602DSR-2K

16 x 2 LCD MODULE, STN GRAY, REFLECTIVE,
12:00 VIEW, 1/16 DUTY, 1/5 BIAS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

LUMEX
INCORPORATED

290 E. HELLEN ROAD
PALATINE, ILLINOIS 60067
PHONE: (847) 359-2790
WEB: <http://www.lumex.com>

DRAWN BY:

SA/BC

CHECKED BY:

APPROVED BY:

DATE: 4-17-00

PAGE: 2 OF 2

SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

[LCM-S01602DSR-2K](#)